



Staffe:					
Comp. / Tratt.	Num.	Diam.(mm)	L (cm)	Peso (kg)	
1 / 1-2-3	15x2	10	183	33,85	
2 / 1-2-3	15x2	10	183	33,85	
3 / 1-2-3	15x2	10	183	33,85	
4 / 1-2-3	15x2	10	183	33,85	

Sezione 1-1

Pos.1

Pos.4

80

40

10

49

2 St. Ø10/25
L = 182

Staffe:					
Comp. / Tratt.	Num.	Diagn.(mm)	L (cm)	Peso (kg)	
1 / 1-2-3	15x2	10	183	33,85	
2 / 1-2-3	15x2	10	183	33,85	
3 / 1-2-3	15x2	10	183	33,85	
4 / 1-2-3	15x2	10	183	33,85	

+60.0

P.Terra Sez. 1-1

The drawing shows a square foundation section with a total width of 35 and a total height of 35. The reinforcement details include:

- Top reinforcement: 4ø14 (verticali)
- Bottom reinforcement: 1+1ø14 (L1) and 1+1ø14 (L2)
- Stirrups: ø8/15, L=128
- Corner reinforcement: 8
- Bottom reinforcement: 2ø8

Currenti:

Pos.4 4ø14 (verticali)

Pos.5 1+1ø14 (L1)

Pos.6 1+1ø14 (L2)

-40.0

Travata: 2

Top View:

- Overall width: 200
- Overall length: 352.5
- End flange width: 40
- Internal spacing: 235
- Stiffeners: 10 (5 on each side)
- Stiffener spacing: 67.5
- Stiffener diameter: $\phi 10/15$
- Stiffener type: St.4 br.

Side View:

- Overall height: 100
- Top flange thickness: 10
- Web thickness: 15
- Bottom flange thickness: 15
- Stiffener height: 40
- Stiffener spacing: 67.5
- Stiffener diameter: $\phi 10/15$
- Stiffener type: St.4 br.

Section 1-1:

- Overall width: 80
- Overall height: 40
- Top flange thickness: 10
- Web thickness: 15
- Bottom flange thickness: 15
- Stiffener height: 40
- Stiffener spacing: 67.5
- Stiffener diameter: $\phi 10/15$
- Stiffener type: St.4 br.

Section 2-2:

- Overall width: 49
- Overall height: 49
- Top flange thickness: 10
- Web thickness: 15
- Bottom flange thickness: 15
- Stiffener height: 40
- Stiffener spacing: 67.5
- Stiffener diameter: $\phi 10/15$
- Stiffener type: St.4 br.

Camp. / Tratt.	Num.	Diam.(mm)	L (cm)	Peso (kg)
1 / 1-2-3	13x2	10	183	29,33

Travata: 4

P5 **P10**

22.5 35 22.5

100 200 235 40 40

Sezione 1-1

Pos.1 **Pos.2**

100 80 40

Stoffe **67.5** **100** **67.5**

Diam./Posso **ø10/15** **ø10/25** **ø10/15**

St.4 br. **St.4 br.** **St.4 br.**

4016 L=370 Pos.1

4016 L=371 Pos.2

2 St. ø10/25

L = 182

Camp. / Tratt.	Num.	Diam.(mm)	L (cm)	Peso (kg)
1 / 1-2-3	13x2	10	183	29,33



COMUNE CODIGORO (FE)
REGIONE EMILIA ROMAGNA

