



Piattaforma polifunzionale Ponticelle

Nulla Osta di Fattibilità (N.O.F.)

D.Lgs. 26 giugno 2015 n. 105 e s.m.i.

RAPPORTO PRELIMINARE DI SICUREZZA Piattaforma polifunzionale Ponticelle

APPENDICE E.1

Output sistema di calcolo EFFECTS

Approvato HA	R. Boschi E. Zamagni		Approvato ER	G. Romano F. Lia		 GOLDER
Controllato HA	M. Facchini L. Pernetta		Controllato ER	E. Lagrotta M. Campello		
Redatto Golder		F. De Giorgi C. Zaffaroni P. Zoppellari				
Cod. Doc. HA	CO 05 RA VA 00 RP DT 10.00		Cod. Doc. ER	160053-ENG-E-E5-2243_All.E.1		
Rev.	00	Data	26/03/2021	Pagine	1 di 169	

SOMMARIO

A TOP EVENT 1.A - PERDITA DA FUSTI/CISTERNETTE E TOP EVENT 3.A – RILASCIO IN FASE DI RICONFEZIONAMENTO.....	4
A.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE).....	4
A.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)	16
A.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO) .	22
B TOP EVENT 1.B - PERDITA DA FUSTI/CISTERNETTE E TOP EVENT 3.B – RILASCIO IN FASE DI RICONFEZIONAMENTO.....	38
B.1 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO).....	38
B.2 INNALZAMENTO DEL PENNACCHIO	40
B.3 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO).....	44
C TOP EVENT 2 A/2.B: PERDITA DA MANICHETTA DI CARICO/SCARICO ATB.....	48
C.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE).....	48
C.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)	60
C.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO) .	66
D TOP EVENT 8 A: ROTTURA/PERDITA DA TUBAZIONE DI TRASFERIMENTO.....	82
D.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE).....	82
D.1.1 Pozza 37 m ²	82
D.1.2 Pozza da 50 m ²	94
D.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)	106
D.2.1 Pozza da 37 m ²	106
D.2.2 Pozza da 50 m ²	112
D.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO)	118
D.3.1 Pozza da 37 m ³	118
D.3.2 Pozza da 50 m ²	134

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	2 di 169
Cod. HA	Descrizione	Rev.	Data	

E TOP EVENT 8.B: ROTTURA/PERDITA DA TUBAZIONE DI TRASFERIMENTO ... 150

E.1 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)	150
E.1.1 Pozza da 37 m ³	150
E.1.2 Pozza da 50 m ³	152
E.2 INNALZAMENTO DEL PENNACCHIO	154
E.2.1 Pozza da 37 m ³	154
E.2.2 Pozza da 50 m ³	158
E.3 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)	162
E.3.1 Pozza da 37 m ³	162
E.3.2 Pozza da 50 m ³	166

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	3 di 169
Cod. HA	Descrizione	Rev.	Data	

A TOP EVENT 1.A - PERDITA DA FUSTI/CISTERNETTE E TOP EVENT 3.A – RILASCIO IN FASE DI RICONFEZIONAMENTO

A.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE)

Model: Pool evaporation - D5 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	1000
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	70
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	4
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,3668
Purple book representative evaporation duration (s)	1392,2
Representative temperature (°C)	19,902
Representative pool diameter (m)	8,373
Density after mixing with air (kg/m3)	1,2215
Total evaporated mass (kg)	510,67
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	55,062
Schmidt number used	1,2728
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	4 di 169
Cod. HA	Descrizione	Rev.	Data	

Contour Dimensions

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous
 Type of continuous source Evaporating pool release
 Mass flow rate of the source (kg/s) 0,3668
 Duration of the release (s) 1392,2
 Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill
 Pasquill stability class D (Neutral)
 Wind speed at 10 m height (m/s) 5
 Predefined wind direction NNE

Environment

Ambient temperature (°C) 20
 Ambient pressure (bar) 1,0133
 North/South latitude of the location (deg) 44
 Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Reporting time flammable cloud Time maximum area cloud
 Concentration averaging time (s) 20
 Use 50% LFL for cloud contour Yes
 Use mass between LFL and UFL Yes
 Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Concentration Results

Flammability threshold concentration (mg/m3) 31394
 Temperature after mixing and expansion (°C)
 Density after mixing and expansion (kg/m3)
 Maximum distance to flammable concentration (m)
 Maximum flammable mass (kg) 0
 Maximum area of flammable cloud (m2) 0
 at Time T (s) 0
 Flammable mass at time t (kg) 0
 Area flammable cloud at time t (m2) 0
 Volume of the flammable cloud at time t (m3)
 Height to LFL at time t (m) 0
 Length of flammable cloud at time t (m) 0
 Width of flammable cloud at time t (m) 0
 Offset flammable cloud at time t (m) 0
 Offset flammable cloud centre at time t (m) 0

Contour Dimensions

Concentration contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	9	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	5 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,3668
Duration of the release (s)	1392,2
Pool surface area (m2)	70
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	No
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	500
Concentration Results	
Flammability threshold concentration (mg/m3)	62788
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	9	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	6 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 1000

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 70

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,21523

Purple book representative evaporation duration (s) 1718,4

Representative temperature (°C) 19,98

Representative pool diameter (m) 9,2205

Density after mixing with air (kg/m3) 1,2284

Total evaporated mass (kg) 369,85

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 66,772

Schmidt number used 1,2728

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	7 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters						
Inputs						
Process Conditions						
Chemical name	ACETONE (DIPPR)					
Source Definition						
Type of neutral gas release	Semi-continuous					
Type of continuos source	Evaporating pool release					
Mass flow rate of the source (kg/s)	0,21523					
Duration of the release (s)	1718,4					
Pool surface area (m2)	70					
Process Dimensions						
Height of release (Z-coordinate) (m)	0					
Meteo Definition						
Meteorological data	Pasquill					
Pasquill stability class	F (Very Stable)					
Wind speed at 10 m height (m/s)	2					
Predefined wind direction	NNE					
Environment						
Ambient temperature (°C)	20					
Ambient pressure (bar)	1,0133					
North/South latitude of the location (deg)	44					
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.					
Accuracy						
Grid resolution	Low					
Reporting						
Reporting time flammable cloud	Time maximum area cloud					
Concentration averaging time (s)	20					
Use 50% LFL for cloud contour	Yes					
Use mass between LFL and UFL	Yes					
Use dynamic concentration presentation	Yes					
Results						
Meteo Definition						
Mixing height used (m)	68,863					
Concentration Results						
Flammability threshold concentration (mg/m3)	31394					
Temperature after mixing and expansion (°C)						
Density after mixing and expansion (kg/m3)						
Maximum distance to flammable concentration (m)						
Maximum flammable mass (kg)	0					
Maximum area of flammable cloud (m2)	0					
at Time T (s)	0					
Flammable mass at time t (kg)	0					
Area flammable cloud at time t (m2)	0					
Volume of the flammable cloud at time t (m3)						
Height to LFL at time t (m)	0					
Length of flammable cloud at time t (m)	0					
Width of flammable cloud at time t (m)	0					
Offset flammable cloud at time t (m)	0					
Offset flammable cloud centre at time t (m)	0					
Contour Dimensions						
Concentration contours						
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]	
IDLH outer contour	23	0	0	9	6037.3	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	8 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,21523				
Duration of the release (s)	1718,4				
Pool surface area (m2)	70				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	20				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	23	0	0	9	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	9 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - D5 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 1000

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 70

Meteo Definition

Wind speed at 10 m height (m/s) 5

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,47693

Purple book representative evaporation duration (s) 1371,8

Representative temperature (°C) 20,98

Representative pool diameter (m) 9,4407

Density after mixing with air (kg/m3) 1,1802

Total evaporated mass (kg) 654,23

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 70

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	10 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,47693				
Duration of the release (s)	1371,8				
Pool surface area (m2)	70				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	5	0	0	9	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	11 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,47693

Duration of the release (s) 1371,8

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Reporting time flammable cloud Time maximum area cloud

Concentration averaging time (s) 20

Use 50% LFL for cloud contour No

Use mass between LFL and UFL Yes

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Concentration Results

Flammability threshold concentration (mg/m3) 62788

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Maximum distance to flammable concentration (m)

Maximum flammable mass (kg) 0

Maximum area of flammable cloud (m2) 0

at Time T (s) 0

Flammable mass at time t (kg) 0

Area flammable cloud at time t (m2) 0

Volume of the flammable cloud at time t (m3)

Height to LFL at time t (m) 0

Length of flammable cloud at time t (m) 0

Width of flammable cloud at time t (m) 0

Offset flammable cloud at time t (m) 0

Offset flammable cloud centre at time t (m) 0

Contour Dimensions

Concentration contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	5	0	0	9	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	12 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 30

Model: Pool Evaporation

version:

v2021.02.8cf0fe9

(23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters**Inputs****Process Conditions**

Chemical name	ACETONE (DIPPR)
---------------	-----------------

Calculation Method

Use which representative rate	First 20% average (flammable)
-------------------------------	-------------------------------

Evaporation from land or water	Land
--------------------------------	------

Type of release in pool	Instantaneous
-------------------------	---------------

Maximum evaluation time for evaporation (s)	1800
---	------

Source Definition

Total mass released (kg)	1000
--------------------------	------

Temperature of the pool (°C)	20
------------------------------	----

Process Dimensions

Type of pool growth on Land	Spreading in bunds
-----------------------------	--------------------

Maximum pool surface area (m2)	70
--------------------------------	----

Meteo Definition

Wind speed at 10 m height (m/s)	2
---------------------------------	---

Environment

Temperature of the subsoil (°C)	40
---------------------------------	----

Ambient temperature (°C)	30
--------------------------	----

Ambient pressure (bar)	1,0133
------------------------	--------

Ambient relative humidity (%)	75
-------------------------------	----

Solar radiation flux	Calculate value
----------------------	-----------------

Cloud cover (%)	0
-----------------	---

Date: day number	20
------------------	----

Date: month number	6
--------------------	---

North/South latitude of the location (deg)	44
--	----

Type of subsoil (evaporation)	Heavy concrete
-------------------------------	----------------

Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
---	--

Results**Source Definition**

Time pool spreading ends (s)	4
------------------------------	---

Time until pool has totally evaporated (s)	
--	--

Purple book representative evaporation rate (kg/s)	0,2911
--	--------

Purple book representative evaporation duration (s)	1688,2
---	--------

Representative temperature (°C)	26,427
---------------------------------	--------

Representative pool diameter (m)	9,4407
----------------------------------	--------

Density after mixing with air (kg/m3)	1,1915
---------------------------------------	--------

Total evaporated mass (kg)	491,44
----------------------------	--------

... duration evaporation time (s)	1799,5
-----------------------------------	--------

Corresponding representative pool surface area (m2)	70
---	----

Schmidt number used	1,2736
---------------------	--------

Dispersion model strategy	
---------------------------	--

Environment

Heat flux from solar radiation (kW/m2)	1,4747
--	--------

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	13 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,2911				
Duration of the release (s)	1688,2				
Pool surface area (m2)	70				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)	1,5614				
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0,1				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	38	0	0	10	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	14 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,2911				
Duration of the release (s)	1688,2				
Pool surface area (m2)	70				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	38	0	0	10	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	15 di 169
Cod. HA	Descrizione	Rev.	Data	

A.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)

Model: pool fire - Acetone (5 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (25/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default
Source Definition	
Total mass released (kg)	1000
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	70
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003
Vulnerability	
Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ((sec*(W/m2)^n))	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333
Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	9,4407
Flame footprint dimensions D,-D,DMW,MW	12;-5;4;9
Calculated pool surface area (m2)	70
Combustion rate (kg/s)	2,66
Duration of fire (s)	375,94
Surface emissive power flame (kW/m2)	32,301
Soot fraction used (-)	0,8
Flame tilt (deg)	54,919
Flame temperature (°C)	598,41
Length of the flame (m)	8,641
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	16 di 169
Cod. HA	Descrizione	Rev.	Data	

Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0069078
Atmospheric Transmissivity at Xd (%)	54,058
Viewfactor at Xd (%)	0,039561
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,026312
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions					
Lethality Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	14	-7	3	16	1
Heat Radiation Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	13	-6	2	15	12,5
7 kW/m2 heat radiation contour	15	-8	3	18	7
5 kW/m2 heat radiation contour	16	-9	3	21	5
3 kW/m2 heat radiation contour	18	-11	3	26	3

Model: pool fire - Acetone (2 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (25/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default
Source Definition	
Total mass released (kg)	1000
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	70
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No
Meteo Definition	
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003
Vulnerability	
Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ($(sec \cdot (W/m2)^n)$)	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333
Accuracy	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	17 di 169
Cod. HA	Descrizione	Rev.	Data	

Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results

Fire Results

Equivalent diameter poolfire (m)	9,4407
Flame footprint dimensions D,-D,DMW,MW	12;-5;4;9
Calculated pool surface area (m2)	70
Combustion rate (kg/s)	2,66
Duration of fire (s)	375,94
Surface emissive power flame (kW/m2)	29,972
Soot fraction used (-)	0,8
Flame tilt (deg)	41,957
Flame temperature (°C)	582,47
Length of the flame (m)	10,474
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,010014
Atmospheric Transmissivity at Xd (%)	53,642
Viewfactor at Xd (%)	0,062287
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,043171
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	13	-7	2	17	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	12	-7	2	15	12,5
7 kW/m2 heat radiation contour	15	-8	2	20	7
5 kW/m2 heat radiation contour	17	-10	3	24	5
3 kW/m2 heat radiation contour	20	-12	3	30	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	18 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: pool fire - Acetone (5 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 1000

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 70

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ((sec*(W/m2)^n)) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

Reporting

Reporting/receiver height (Zd) (m) 1,7

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m) 9,4407

Flame footprint dimensions D,-D,DMW,MW 12;-5;4;9

Calculated pool surface area (m2) 70

Combustion rate (kg/s) 2,66

Duration of fire (s) 375,94

Surface emissive power flame (kW/m2) 31,985

Soot fraction used (-) 0,8

Flame tilt (deg) 54,807

Flame temperature (°C) 596,7

Length of the flame (m) 8,8582

Weight ratio of HCL/chemical (%) 0

Weight ratio of NO2/chemical (%) 0

Weight ratio of SO2/chemical (%) 0

Weight ratio of CO2/chemical (%) 227,37

Weight ratio of H2O/chemical (%) 93,091

Heat radiation at Xd (kW/m2) 0,0064091

Atmospheric Transmissivity at Xd (%) 49,259

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	19 di 169
Cod. HA	Descrizione	Rev.	Data	

Viewfactor at Xd (%)	0,040679
Heat radiation dose at Xd ($s \cdot (kW/m^2)^{4/3}$)	0,02381
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	14	-7	3	16	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	13	-6	2	14	12,5
7 kW/m2 heat radiation contour	15	-8	3	18	7
5 kW/m2 heat radiation contour	16	-9	3	21	5
3 kW/m2 heat radiation contour	18	-11	3	26	3

Model: pool fire - Acetone (2 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 1000

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 70

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ($(sec \cdot (W/m^2)^n)$) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	20 di 169
Cod. HA	Descrizione	Rev.	Data	

Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	9,4407
Flame footprint dimensions D,-D,DMW,MW	12;-5;4;9
Calculated pool surface area (m2)	70
Combustion rate (kg/s)	2,66
Duration of fire (s)	375,94
Surface emissive power flame (kW/m2)	29,692
Soot fraction used (-)	0,8
Flame tilt (deg)	41,82
Flame temperature (°C)	580,91
Length of the flame (m)	10,738
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0092626
Atmospheric Transmissivity at Xd (%)	48,759
Viewfactor at Xd (%)	0,06398
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,038905
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions					
Lethality Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	13	-7	2	17	1
Heat Radiation Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	12	-6	2	15	12,5
7 kW/m2 heat radiation contour	15	-8	2	20	7
5 kW/m2 heat radiation contour	17	-9	3	23	5
3 kW/m2 heat radiation contour	20	-12	3	29	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	21 di 169
Cod. HA	Descrizione	Rev.	Data	

A.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO)

Model: Pool evaporation - D5 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	600
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	70
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	4,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,11448
Purple book representative evaporation duration (s)	1777,8
Representative temperature (°C)	13,038
Representative pool diameter (m)	9,4407
Density after mixing with air (kg/m3)	1,2016
Total evaporated mass (kg)	203,53
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	70
Schmidt number used	0,91478
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	22 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,11448

Duration of the release (s) 1777,8

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 90,941

Maximum concentration at Zd (mg/m3) 690,53

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	23 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,11448

Duration of the release (s) 1777,8

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 90,941

Maximum concentration at Zd (mg/m3) 690,53

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	24 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,11448

Duration of the release (s) 1777,8

Pool surface area (m²) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 90,941

Maximum concentration at Zd (mg/m³) 690,53

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	25 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 600

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 70

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,084944

Purple book representative evaporation duration (s) 1783,5

Representative temperature (°C) 20,99

Representative pool diameter (m) 9,4407

Density after mixing with air (kg/m3) 1,2022

Total evaporated mass (kg) 151,5

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 70

Schmidt number used 0,91478

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	26 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,084944

Duration of the release (s) 1783,5

Pool surface area (m²) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 667,72

Maximum concentration at Zd (mg/m³) 1280,3

...at distance (m) 28,1

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	27 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,084944

Duration of the release (s) 1783,5

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, $x/h < 15$.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 667,72

Maximum concentration at Zd (mg/m3) 1280,3

...at distance (m) 28,1

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	28 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,084944
Duration of the release (s)	1783,5
Pool surface area (m2)	70
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	799,38
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	68,863
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	799,38
Concentration at (Xd, Yd, Zd, t) (mg/m3)	667,72
Maximum concentration at Zd (mg/m3)	1280,3
...at distance (m)	27,8
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
User defined concentration at 1.7m at 600s	83	10	16	9	799,38
User defined concentration outer contour at 1.7m	83	10	16	9	799,38

Model: Pool evaporation - D5 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	29 di 169
Cod. HA	Descrizione	Rev.	Data	

advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	600
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	70
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	40
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition	
Time pool spreading ends (s)	4,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,16077
Purple book representative evaporation duration (s)	1696,5
Representative temperature (°C)	19,489
Representative pool diameter (m)	9,4407
Density after mixing with air (kg/m3)	1,1562
Total evaporated mass (kg)	272,74
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	70
Schmidt number used	0,91541
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	30 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,16077

Duration of the release (s) 1696,5

Pool surface area (m²) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 127,71

Maximum concentration at Zd (mg/m³) 969,71

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	31 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,16077
Duration of the release (s)	1696,5
Pool surface area (m2)	70
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	No
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7993,8
Concentration at (Xd, Yd, Zd, t) (mg/m3)	127,71
Maximum concentration at Zd (mg/m3)	969,71
...at distance (m)	8
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	32 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,16077
Duration of the release (s)	1696,5
Pool surface area (m2)	70
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	799,38
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	799,38
Concentration at (Xd, Yd, Zd, t) (mg/m3)	127,71
Maximum concentration at Zd (mg/m3)	969,71
...at distance (m)	8
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
User defined concentration at 1.7m at 600s	18	4	5	8	799,38
User defined concentration outer contour at 1.7m	18	4	5	8	799,38

Model: Pool evaporation - F2 30 tossico

Model: Pool Evaporation

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	33 di 169
Cod. HA	Descrizione	Rev.	Data	

version: v2021.02.8cf0fe9 (23/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	600
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	70
Meteo Definition	
Wind speed at 10 m height (m/s)	2
Environment	
Temperature of the subsoil (°C)	40
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	4,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,12341
Purple book representative evaporation duration (s)	1710
Representative temperature (°C)	28,599
Representative pool diameter (m)	9,4407
Density after mixing with air (kg/m3)	1,1572
Total evaporated mass (kg)	211,04
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	70
Schmidt number used	0,91541
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4747
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	34 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,12341

Duration of the release (s) 1710

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 970,12

Maximum concentration at Zd (mg/m3) 1860,1

...at distance (m) 28,1

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	35 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,12341

Duration of the release (s) 1710

Pool surface area (m2) 70

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, $x/h < 15$.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 970,12

Maximum concentration at Zd (mg/m3) 1860,1

...at distance (m) 27,8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	36 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	METHANOL (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,12341				
Duration of the release (s)	1710				
Pool surface area (m2)	70				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	N				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Time t after start release (s)	600				
Concentration averaging time (s)	600				
Reporting distance (Xd) (m)	100				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	799,38				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692				
Concentration Results					
Threshold concentration used (mg/m3)	799,38				
Concentration at (Xd, Yd, Zd, t) (mg/m3)	970,12				
Maximum concentration at Zd (mg/m3)	1860,1				
...at distance (m)	28,1				
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728				
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
User defined concentration outer contour at 1.7m	119	8	26	10	799,38
User defined concentration at 1.7m at 600s	119	8	26	10	799,38

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	37 di 169
Cod. HA	Descrizione	Rev.	Data	

B TOP EVENT 1.B - PERDITA DA FUSTI/CISTERNETTE E TOP EVENT 3.B – RILASCIO IN FASE DI RICONFEZIONAMENTO

B.1 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)

Model: Combustion and toxic combustion products 20°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (23/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters	
Inputs	
Process Conditions	
Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)
Calculation Method	
NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8
Source Definition	
Total mass released (kg)	600
Surface of the fire (m ²)	70
Environment	
Ambient temperature (°C)	20
Results	
Process Conditions	
Averaged molecular formula used	C ₂ H ₄ Cl ₂
Source Definition	
Calculated molecular mass of the chemical (kg/kmol)	98,959
Fire Results	
Combustion rate of the chemical (kg/s)	2,7937
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	9,4407
(Convective) Heat production fire (MW)	12,478
Duration of the fire (s)	214,77
Total formation rate of combustion products (kg/s)	4,1283
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	2,0518
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,50177
H ₂ O formation rate (kg/s)	1,0272
Soot formation rate (kg/s)	0,54751
Height of the Flame (m)	12,19
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	38 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Combustion and toxic combustion products 30°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (23/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters

Inputs

Process Conditions

Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)
Calculation Method	
NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8

Source Definition

Total mass released (kg)	600
Surface of the fire (m ²)	70

Environment

Ambient temperature (°C)	30
--------------------------	----

Results

Process Conditions

Averaged molecular formula used	C ₂ H ₄ Cl ₂
---------------------------------	---

Source Definition

Calculated molecular mass of the chemical (kg/kmol)	98,959
---	--------

Fire Results

Combustion rate of the chemical (kg/s)	2,8925
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	9,4407
(Convective) Heat production fire (MW)	12,919
Duration of the fire (s)	207,43
Total formation rate of combustion products (kg/s)	4,2743
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	2,1244
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,51951
H ₂ O formation rate (kg/s)	1,0635
Soot formation rate (kg/s)	0,56687
Height of the Flame (m)	12,451

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	39 di 169
Cod. HA	Descrizione	Rev.	Data	

B.2 INNALZAMENTO DEL PENNACCHIO

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (23/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res.

Des, 67, 348-352.

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Mass flow rate of the source (kg/s)	2,0518
Process Dimensions	
Release height (Stack height) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	20
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Reporting	
Concentration averaging time (s)	600
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
End point for graphs (m)	10000
Fire Results	
(Representative) Diameter of fire (m)	9,4407
(Convective) Heat production fire (MW)	12,478

Results	
Meteo Definition	
Mixing height used (m)	500
Concentration Results	
Max (center) height of plume (m)	122,26
Distance to max plume height (m)	794,33
Penetration fraction (-)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH Max	285	1	129	43	75,802
IDLH at Zd	107	1	5	39	75,802
User defined concentration at Zd	228	1	89	55	7,58
User defined concentration Max	1245	1	623	137	7,58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	40 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (23/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

001, 01, 010 002:

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	2,1244				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	30				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	9,4407				
(Convective) Heat production fire (MW)	12,919				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Max (center) height of plume (m)	125				
Distance to max plume height (m)	794,33				
Penetration fraction (-)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH at Zd	105	1	5	39	75,802
IDLH Max	292	1	132	43	75,802
User defined concentration at Zd	224	1	81	54	7,58
User defined concentration Max	1274	1	624	140	7,58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	42 di 169
Cod. HA	Descrizione	Rev.	Data	

B.3 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)

Model: Neutral Gas Dispersion: Concentration HCl – LOC -Classe di Pasquill D5 20°C

Model: Neutral Gas - Concentration

version:

v2021.02.022757e

(23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	2,0518
Duration of the release (min)	3,58
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	122,26
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,0040552
Maximum concentration at Zd (mg/m3)	2,0956
...at distance (m)	1522,4
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,82557
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2535
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 20°C LOC

Model: Neutral Gas - Concentration

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	44 di 169
Cod. HA	Descrizione	Rev.	Data	

version:

v2021.02.022757e

(23/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters**Inputs****Process Conditions**

Chemical name HYDROGEN CHLORIDE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source User defined window

Mass flow rate of the source (kg/s) 2,0518

Duration of the release (min) 3,58

Length source in wind (x) direction (m) 0

Width source in crosswind (y) direction (m) 0

Height source in vertical (z) direction (m) 0

Process Dimensions

Height of release (Z-coordinate) (m) 69

Offset X direction (distance) start dispersion (m) 0

Offset Z direction (height) start dispersion (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction User defined

Wind comes from (North = 0 degrees) (deg) 270

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0151

North/South latitude of the location (deg) 43

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution High

Reporting

Time t after start release (s) 1800

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 10000

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 7,58

Use dynamic concentration presentation No

Results**Meteo Definition**

Mixing height used (m) 69,499

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7,58

Concentration at (Xd, Yd, Zd, t) (mg/m3) 0,18723

Maximum concentration at Zd (mg/m3) 6,719

...at distance (m) 4679,4

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,01672

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,024437

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill D5 30°C LOC

Model: Neutral Gas - Concentration

version:

v2021.02.022757e

(24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters**Inputs**

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	45 di 169
Cod. HA	Descrizione	Rev.	Data	

Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	2,1244
Duration of the release (s)	207,43
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	125
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No

Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,0036505
Maximum concentration at Zd (mg/m3)	1,9936
...at distance (m)	1522,4
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,82402
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2525
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 30°C LOC

Model: Neutral Gas – Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	46 di 169
Cod. HA	Descrizione	Rev.	Data	

Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	2,1244
Duration of the release (s)	207,43
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	69
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	69,499
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,18142
Maximum concentration at Zd (mg/m3)	6,896
...at distance (m)	4646,3
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,01672
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,024437
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	47 di 169
Cod. HA	Descrizione	Rev.	Data	

C TOP EVENT 2 A/2.B: PERDITA DA MANICHETTA DI CARICO/SCARICO ATB

C.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE)

Model: Pool evaporation - D5 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	10
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,071815
Purple book representative evaporation duration (s)	1675,5
Representative temperature (°C)	19,553
Representative pool diameter (m)	3,5682
Density after mixing with air (kg/m3)	1,2102
Total evaporated mass (kg)	120,33
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	10
Schmidt number used	1,2728
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	48 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuous source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,071815				
Duration of the release (s)	1675,5				
Pool surface area (m2)	10				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	20				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	1	0	0	4	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	49 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters						
Inputs						
Process Conditions						
Chemical name	ACETONE (DIPPR)					
Source Definition						
Type of neutral gas release	Semi-continuous					
Type of continuos source	Evaporating pool release					
Mass flow rate of the source (kg/s)	0,071815					
Duration of the release (s)	1675,5					
Pool surface area (m2)	10					
Process Dimensions						
Height of release (Z-coordinate) (m)	0					
Meteo Definition						
Meteorological data	Pasquill					
Pasquill stability class	D (Neutral)					
Wind speed at 10 m height (m/s)	5					
Predefined wind direction	NNE					
Environment						
Ambient temperature (°C)	20					
Ambient pressure (bar)	1,0133					
North/South latitude of the location (deg)	44					
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.					
Accuracy						
Grid resolution	Low					
Reporting						
Reporting time flammable cloud	Time maximum area cloud					
Concentration averaging time (s)	20					
Use 50% LFL for cloud contour	No					
Use mass between LFL and UFL	Yes					
Use dynamic concentration presentation	Yes					
Results						
Meteo Definition						
Mixing height used (m)	500					
Concentration Results						
Flammability threshold concentration (mg/m3)	62788					
Temperature after mixing and expansion (°C)						
Density after mixing and expansion (kg/m3)						
Maximum distance to flammable concentration (m)						
Maximum flammable mass (kg)	0					
Maximum area of flammable cloud (m2)	0					
at Time T (s)	0					
Flammable mass at time t (kg)	0					
Area flammable cloud at time t (m2)	0					
Volume of the flammable cloud at time t (m3)						
Height to LFL at time t (m)	0					
Length of flammable cloud at time t (m)	0					
Width of flammable cloud at time t (m)	0					
Offset flammable cloud at time t (m)	0					
Offset flammable cloud centre at time t (m)	0					
Contour Dimensions						
Concentration contours						
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]	
IDLH outer contour	1	0	0	4	6037.3	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	50 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 10

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s)

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,035661

Purple book representative evaporation duration (s) 1774,5

Representative temperature (°C) 19,909

Representative pool diameter (m) 3,5682

Density after mixing with air (kg/m3) 1,2125

Total evaporated mass (kg) 63,282

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 10

Schmidt number used 1,2728

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

Model: Neutral Gas Dispersion: Flammable Cloud - F2 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	51 di 169
Cod. HA	Descrizione	Rev.	Data	

Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,035661
Duration of the release (s)	1774,5
Pool surface area (m2)	10
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	Yes
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	68,863
Concentration Results	
Flammability threshold concentration (mg/m3)	31394
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	5	0	0	4	6037,3

Model: Neutral Gas Dispersion: Flammable Cloud - F2 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	52 di 169
Cod. HA	Descrizione	Rev.	Data	

Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,035661
Duration of the release (s)	1774,5
Pool surface area (m2)	10
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	No
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	68,863
Concentration Results	
Flammability threshold concentration (mg/m3)	62788
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	5	0	0	4	6037,3

Model: Pool evaporation - D5 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	53 di 169
Cod. HA	Descrizione	Rev.	Data	

Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	10
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	40
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,07328
Purple book representative evaporation duration (s)	1722
Representative temperature (°C)	20,058
Representative pool diameter (m)	3,5682
Density after mixing with air (kg/m3)	1,1651
Total evaporated mass (kg)	126,19
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	10
Schmidt number used	1,2736
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4747
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	54 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,07328				
Duration of the release (s)	1722				
Pool surface area (m2)	10				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	1	0	0	4	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	55 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,07328				
Duration of the release (s)	1722				
Pool surface area (m2)	10				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	1	0	0	4	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	56 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 10

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s)

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,037038

Purple book representative evaporation duration (s) 1790,4

Representative temperature (°C) 20,843

Representative pool diameter (m) 3,5682

Density after mixing with air (kg/m3) 1,1678

Total evaporated mass (kg) 66,314

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 10

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	57 di 169
Cod. HA	Descrizione	Rev.	Data	

Neutral Gas Dispersion: Flammable Cloud - F2 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,037038
Duration of the release (s)	1790,4
Pool surface area (m2)	10
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	Yes
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	68,863
Concentration Results	
Flammability threshold concentration (mg/m3)	31394
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	6	0	0	4	6037,3

Model: Neutral Gas Dispersion: Flammable Cloud - F2 _LEL

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	58 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters**Inputs****Process Conditions**

Chemical name ACETONE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,037038

Duration of the release (s) 1790,4

Pool surface area (m²) 10**Process Dimensions**

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Reporting time flammable cloud Time maximum area cloud

Concentration averaging time (s) 20

Use 50% LFL for cloud contour No

Use mass between LFL and UFL Yes

Use dynamic concentration presentation Yes

Results**Meteo Definition**

Mixing height used (m) 68,863

Concentration ResultsFlammability threshold concentration (mg/m³) 62788

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Maximum distance to flammable concentration (m)

Maximum flammable mass (kg) 0

Maximum area of flammable cloud (m²) 0

at Time T (s) 0

Flammable mass at time t (kg) 0

Area flammable cloud at time t (m²) 0Volume of the flammable cloud at time t (m³)

Height to LFL at time t (m) 0

Length of flammable cloud at time t (m) 0

Width of flammable cloud at time t (m) 0

Offset flammable cloud at time t (m) 0

Offset flammable cloud centre at time t (m) 0

Contour Dimensions**Concentration contours**

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m ³]
IDLH outer contour	6	0	0	4	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	59 di 169
Cod. HA	Descrizione	Rev.	Data	

C.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)

Model: pool fire - Acetone (5 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	10
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003
Vulnerability	
Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ((sec*(W/m2)^n))	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333
Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200
Results	
Fire Results	
Equivalent diameter poolfire (m)	3,5682
Flame footprint dimensions D,-D,DMW,MW	5;-2;2;4
Calculated pool surface area (m2)	10
Combustion rate (kg/s)	0,38
Duration of fire (s)	11053
Surface emissive power flame (kW/m2)	29,242
Soot fraction used (-)	0,8
Flame tilt (deg)	58,181
Flame temperature (°C)	577,28
Length of the flame (m)	4,2266
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	60 di 169
Cod. HA	Descrizione	Rev.	Data	

Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,001003
Atmospheric Transmissivity at Xd (%)	53,196
Viewfactor at Xd (%)	0,0064481
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,0020081
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	6	-2	1	6	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	6	-2	1	5	12,5
7 kW/m2 heat radiation contour	6	-3	1	7	7
5 kW/m2 heat radiation contour	7	-4	1	8	5
3 kW/m2 heat radiation contour	7	-5	1	10	3

Model: pool fire - Acetone (2 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B, ~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 10

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ($(sec \cdot (W/m2)^n)$) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	61 di 169
Cod. HA	Descrizione	Rev.	Data	

Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	3,5682
Flame footprint dimensions D,-D,DMW,MW	5;-2;2;4
Calculated pool surface area (m2)	10
Combustion rate (kg/s)	0,38
Duration of fire (s)	11053
Surface emissive power flame (kW/m2)	27,268
Soot fraction used (-)	0,8
Flame tilt (deg)	46,012
Flame temperature (°C)	562,76
Length of the flame (m)	5,1234
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0014917
Atmospheric Transmissivity at Xd (%)	52,822
Viewfactor at Xd (%)	0,010356
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,0034088
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions					
Lethality Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	6	-3	1	7	1
Heat Radiation Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	6	-2	1	6	12,5
7 kW/m2 heat radiation contour	7	-3	1	8	7
5 kW/m2 heat radiation contour	7	-4	1	10	5
3 kW/m2 heat radiation contour	9	-5	1	12	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	62 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: pool fire - Acetone (5 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Semi-continuous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Mass flow rate of the source (kg/s) 14

Duration of the release (min) 5

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 10

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ((sec*(W/m2)^n)) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

Reporting

Reporting/receiver height (Zd) (m) 1,7

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m) 3,5682

Flame footprint dimensions D,-D,DMW,MW 5;-2;2;4

Calculated pool surface area (m2) 10

Combustion rate (kg/s) 0,38

Duration of fire (s) 11053

Surface emissive power flame (kW/m2) 28,973

Soot fraction used (-) 0,8

Flame tilt (deg) 58,077

Flame temperature (°C) 575,78

Length of the flame (m) 4,3328

Weight ratio of HCL/chemical (%) 0

Weight ratio of NO2/chemical (%) 0

Weight ratio of SO2/chemical (%) 0

Weight ratio of CO2/chemical (%) 227,37

Weight ratio of H2O/chemical (%) 93,091

Heat radiation at Xd (kW/m2) 0,00092817

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	63 di 169
Cod. HA	Descrizione	Rev.	Data	

Atmospheric Transmissivity at Xd (%)	48,283
Viewfactor at Xd (%)	0,0066351
Heat radiation dose at Xd ($s \cdot (kW/m^2)^{4/3}$)	0,0018108
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	6	-2	1	6	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	6	-2	1	5	12,5
7 kW/m2 heat radiation contour	6	-3	1	7	7
5 kW/m2 heat radiation contour	7	-4	1	8	5
3 kW/m2 heat radiation contour	7	-5	1	10	3

Model: pool fire - Acetone (2 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Semi-continuous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Mass flow rate of the source (kg/s) 14

Duration of the release (min) 5

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 10

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ($(sec \cdot (W/m^2)^n)$) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	64 di 169
Cod. HA	Descrizione	Rev.	Data	

Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	3,5682
Flame footprint dimensions D,-D,DMW,MW	6;-2;2;4
Calculated pool surface area (m2)	10
Combustion rate (kg/s)	0,38
Duration of fire (s)	11053
Surface emissive power flame (kW/m2)	27,032
Soot fraction used (-)	0,8
Flame tilt (deg)	45,881
Flame temperature (°C)	561,43
Length of the flame (m)	5,2522
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0013756
Atmospheric Transmissivity at Xd (%)	47,835
Viewfactor at Xd (%)	0,010638
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,0030597
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions					
Lethality Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	6	-3	1	7	1
Heat Radiation Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	6	-2	1	6	12,5
7 kW/m2 heat radiation contour	7	-3	1	8	7
5 kW/m2 heat radiation contour	7	-4	1	9	5
3 kW/m2 heat radiation contour	9	-5	1	12	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	65 di 169
Cod. HA	Descrizione	Rev.	Data	

C.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO)

Model: Pool evaporation - D5 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	2520
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	10
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,024686
Purple book representative evaporation duration (s)	1733,4
Representative temperature (°C)	18,805
Representative pool diameter (m)	3,5682
Density after mixing with air (kg/m3)	1,201
Total evaporated mass (kg)	42,791
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	10
Schmidt number used	0,91478
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613
Contour Dimensions	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	66 di 169
Cod. HA	Descrizione	Rev.	Data	

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,024686
Duration of the release (s)	1733,4
Pool surface area (m2)	10
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	32375
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	32375
Concentration at (Xd, Yd, Zd, t) (mg/m3)	20,532
Maximum concentration at Zd (mg/m3)	383,6
...at distance (m)	7,2
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,024686
Duration of the release (s)	1733,4

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	67 di 169
Cod. HA	Descrizione	Rev.	Data	

Pool surface area (m2)	10
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	No
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7993,8
Concentration at (Xd, Yd, Zd, t) (mg/m3)	20,532
Maximum concentration at Zd (mg/m3)	383,6
...at distance (m)	7,2
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	68 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,024686

Duration of the release (s) 1733,4

Pool surface area (m2) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m3) 20,532

Maximum concentration at Zd (mg/m3) 383,6

...at distance (m) 7,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	69 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 2520

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 10

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s)

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,012817

Purple book representative evaporation duration (s) 1797,9

Representative temperature (°C) 19,96

Representative pool diameter (m) 3,5682

Density after mixing with air (kg/m3) 1,2011

Total evaporated mass (kg) 23,043

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 10

Schmidt number used 0,91478

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	70 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,012817

Duration of the release (s) 1797,9

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 119,28

Maximum concentration at Zd (mg/m³) 456,38

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	71 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,012817

Duration of the release (s) 1797,9

Pool surface area (m2) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 119,28

Maximum concentration at Zd (mg/m3) 456,38

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	72 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,012817

Duration of the release (s) 1797,9

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 119,28

Maximum concentration at Zd (mg/m³) 456,38

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	73 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - D5 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 2520

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 10

Meteo Definition

Wind speed at 10 m height (m/s) 5

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s)

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,026364

Purple book representative evaporation duration (s) 1757,5

Representative temperature (°C) 20,097

Representative pool diameter (m) 3,5682

Density after mixing with air (kg/m3) 1,1552

Total evaporated mass (kg) 46,335

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 10

Schmidt number used 0,91541

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	74 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,026364

Duration of the release (s) 1757,5

Pool surface area (m2) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 21,927

Maximum concentration at Zd (mg/m3) 409,67

...at distance (m) 7,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	75 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,026364

Duration of the release (s) 1757,5

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m³) 21,927

Maximum concentration at Zd (mg/m³) 409,67

...at distance (m) 7,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	76 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,026364

Duration of the release (s) 1757,5

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 21,927

Maximum concentration at Zd (mg/m³) 409,67

...at distance (m) 7,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	77 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 2520

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 10

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s)

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,014124

Purple book representative evaporation duration (s) 1767,5

Representative temperature (°C) 21,886

Representative pool diameter (m) 3,5682

Density after mixing with air (kg/m3) 1,1554

Total evaporated mass (kg) 24,964

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 10

Schmidt number used 0,91541

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	78 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,014124

Duration of the release (s) 1767,5

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 131,44

Maximum concentration at Zd (mg/m³) 502,94

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	79 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,014124

Duration of the release (s) 1767,5

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m³) 131,44

Maximum concentration at Zd (mg/m³) 502,94

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	80 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,014124

Duration of the release (s) 1767,5

Pool surface area (m²) 10

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 131,44

Maximum concentration at Zd (mg/m³) 502,94

...at distance (m) 20

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	81 di 169
Cod. HA	Descrizione	Rev.	Data	

D TOP EVENT 8 A: ROTTURA/PERDITA DA TUBAZIONE DI TRASFERIMENTO

D.1 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI INFIAMMABILI – FLASH FIRE (ACETONE)

D.1.1 Pozza 37 m²

Model: Pool evaporation - D5 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	37
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard

Results	
Source Definition	
Time pool spreading ends (s)	1,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,23907
Purple book representative evaporation duration (s)	1508,3
Representative temperature (°C)	19,987
Representative pool diameter (m)	6,6738
Density after mixing with air (kg/m3)	1,2177
Total evaporated mass (kg)	360,59
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	34,981
Schmidt number used	1,2728
Dispersion model strategy	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	82 di 169
Cod. HA	Descrizione	Rev.	Data	

Environment

Heat flux from solar radiation (kW/m2)	1,4613
--	--------

Contour Dimensions

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters**Inputs****Process Conditions**

Chemical name	ACETONE (DIPPR)
---------------	-----------------

Source Definition

Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,23907
Duration of the release (s)	1508,3
Pool surface area (m2)	37

Process Dimensions

Height of release (Z-coordinate) (m)	0
--------------------------------------	---

Meteo Definition

Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE

Environment

Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution	Low
-----------------	-----

Reporting

Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	Yes
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes

Results**Meteo Definition**

Mixing height used (m)	500
------------------------	-----

Concentration Results

Flammability threshold concentration (mg/m3)	31394
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	83 di 169
Cod. HA	Descrizione	Rev.	Data	

Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	7	6037,3

Model: Neutral Gas Dispersion: Flammable Cloud - D5_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,23907

Duration of the release (s) 1508,3

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Reporting time flammable cloud Time maximum area cloud

Concentration averaging time (s) 20

Use 50% LFL for cloud contour No

Use mass between LFL and UFL Yes

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Concentration Results

Flammability threshold concentration (mg/m3) 62788

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Maximum distance to flammable concentration (m)

Maximum flammable mass (kg) 0

Maximum area of flammable cloud (m2) 0

at Time T (s) 0

Flammable mass at time t (kg) 0

Area flammable cloud at time t (m2) 0

Volume of the flammable cloud at time t (m3)

Height to LFL at time t (m) 0

Length of flammable cloud at time t (m) 0

Width of flammable cloud at time t (m) 0

Offset flammable cloud at time t (m) 0

Offset flammable cloud centre at time t (m) 0

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	84 di 169
Cod. HA	Descrizione	Rev.	Data	

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	7	6037,3

Model: Pool evaporation -F2 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	37
Meteo Definition	
Wind speed at 10 m height (m/s)	2
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard

Results	
Source Definition	
Time pool spreading ends (s)	1,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,122
Purple book representative evaporation duration (s)	1746,5
Representative temperature (°C)	19,998
Representative pool diameter (m)	6,826
Density after mixing with air (kg/m3)	1,2219
Total evaporated mass (kg)	213,07
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	36,595
Schmidt number used	1,2728
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613

Contour Dimensions	
--------------------	--

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	85 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuous source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,122				
Duration of the release (s)	1746,5				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	20				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	15	0	0	7	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	86 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,122				
Duration of the release (s)	1746,5				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	20				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	15	0	0	7	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	87 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - D5 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 37

Meteo Definition

Wind speed at 10 m height (m/s) 5

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 1,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,25496

Purple book representative evaporation duration (s) 1606,6

Representative temperature (°C) 20,316

Representative pool diameter (m) 6,8637

Density after mixing with air (kg/m3) 1,1736

Total evaporated mass (kg) 409,63

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 37

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	88 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,25496				
Duration of the release (s)	1606,6				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	7	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	89 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuous source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,25496				
Duration of the release (s)	1606,6				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	3	0	0	7	6037.3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	90 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 37

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 1,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,13746

Purple book representative evaporation duration (s) 1777,1

Representative temperature (°C) 22,692

Representative pool diameter (m) 6,8637

Density after mixing with air (kg/m3) 1,1796

Total evaporated mass (kg) 244,28

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 37

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	91 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,13746				
Duration of the release (s)	1777,1				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	Yes				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	31394				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	18	0	0	7	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	92 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,13746				
Duration of the release (s)	1777,1				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	18	0	0	7	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	93 di 169
Cod. HA	Descrizione	Rev.	Data	

D.1.2 Pozza da 50 m²

Model: Pool evaporation - D5 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	250
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	50
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	4,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,25368
Purple book representative evaporation duration (s)	816,7
Representative temperature (°C)	19,739
Representative pool diameter (m)	6,9124
Density after mixing with air (kg/m3)	1,2182
Total evaporated mass (kg)	207,18
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	37,528
Schmidt number used	1,2728
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	94 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,25368

Duration of the release (s) 816,7

Pool surface area (m2) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Reporting time flammable cloud Time maximum area cloud

Concentration averaging time (s) 20

Use 50% LFL for cloud contour Yes

Use mass between LFL and UFL Yes

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Concentration Results

Flammability threshold concentration (mg/m3) 31394

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Maximum distance to flammable concentration (m)

Maximum flammable mass (kg) 0

Maximum area of flammable cloud (m2) 0

at Time T (s) 0

Flammable mass at time t (kg) 0

Area flammable cloud at time t (m2) 0

Volume of the flammable cloud at time t (m3)

Height to LFL at time t (m) 0

Length of flammable cloud at time t (m) 0

Width of flammable cloud at time t (m) 0

Offset flammable cloud at time t (m) 0

Offset flammable cloud centre at time t (m) 0

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	95 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,25368
Duration of the release (s)	816,7
Pool surface area (m2)	50
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	No
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	500
Concentration Results	
Flammability threshold concentration (mg/m3)	62788
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	96 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 20

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 250

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,15334

Purple book representative evaporation duration (s) 1190,7

Representative temperature (°C) 19,944

Representative pool diameter (m) 7,7025

Density after mixing with air (kg/m3) 1,2243

Total evaporated mass (kg) 182,57

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 46,597

Schmidt number used 1,2728

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	97 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,15334
Duration of the release (s)	1190,7
Pool surface area (m2)	50
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	Yes
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	68,863
Concentration Results	
Flammability threshold concentration (mg/m3)	31394
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	17	0	0	8	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	98 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters						
Inputs						
Process Conditions						
Chemical name	ACETONE (DIPPR)					
Source Definition						
Type of neutral gas release	Semi-continuous					
Type of continuos source	Evaporating pool release					
Mass flow rate of the source (kg/s)	0,15334					
Duration of the release (s)	1190,7					
Pool surface area (m2)	50					
Process Dimensions						
Height of release (Z-coordinate) (m)	0					
Meteo Definition						
Meteorological data	Pasquill					
Pasquill stability class	F (Very Stable)					
Wind speed at 10 m height (m/s)	2					
Predefined wind direction	NNE					
Environment						
Ambient temperature (°C)	20					
Ambient pressure (bar)	1,0133					
North/South latitude of the location (deg)	44					
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.					
Accuracy						
Grid resolution	Low					
Reporting						
Reporting time flammable cloud	Time maximum area cloud					
Concentration averaging time (s)	20					
Use 50% LFL for cloud contour	No					
Use mass between LFL and UFL	Yes					
Use dynamic concentration presentation	Yes					
Results						
Meteo Definition						
Mixing height used (m)	68,863					
Concentration Results						
Flammability threshold concentration (mg/m3)	62788					
Temperature after mixing and expansion (°C)						
Density after mixing and expansion (kg/m3)						
Maximum distance to flammable concentration (m)						
Maximum flammable mass (kg)	0					
Maximum area of flammable cloud (m2)	0					
at Time T (s)	0					
Flammable mass at time t (kg)	0					
Area flammable cloud at time t (m2)	0					
Volume of the flammable cloud at time t (m3)						
Height to LFL at time t (m)	0					
Length of flammable cloud at time t (m)	0					
Width of flammable cloud at time t (m)	0					
Offset flammable cloud at time t (m)	0					
Offset flammable cloud centre at time t (m)	0					
Contour Dimensions						
Concentration contours						
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]	
IDLH outer contour	17	0	0	8	6037.3	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	99 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - D5 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 250

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 5

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,37007

Purple book representative evaporation duration (s) 609,94

Representative temperature (°C) 22,663

Representative pool diameter (m) 7,9788

Density after mixing with air (kg/m3) 1,1778

Total evaporated mass (kg) 225,72

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 50

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	100 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5 _0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters						
Inputs						
Process Conditions						
Chemical name	ACETONE (DIPPR)					
Source Definition						
Type of neutral gas release	Semi-continuous					
Type of continuos source	Evaporating pool release					
Mass flow rate of the source (kg/s)	0,37007					
Duration of the release (s)	609,94					
Pool surface area (m2)	50					
Process Dimensions						
Height of release (Z-coordinate) (m)	0					
Meteo Definition						
Meteorological data	Pasquill					
Pasquill stability class	D (Neutral)					
Wind speed at 10 m height (m/s)	5					
Predefined wind direction	NNE					
Environment						
Ambient temperature (°C)	30					
Ambient pressure (bar)	1,0133					
North/South latitude of the location (deg)	44					
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.					
Accuracy						
Grid resolution	Low					
Reporting						
Reporting time flammable cloud	Time maximum area cloud					
Concentration averaging time (s)	20					
Use 50% LFL for cloud contour	Yes					
Use mass between LFL and UFL	Yes					
Use dynamic concentration presentation	Yes					
Results						
Meteo Definition						
Mixing height used (m)	500					
Concentration Results						
Flammability threshold concentration (mg/m3)	31394					
Temperature after mixing and expansion (°C)						
Density after mixing and expansion (kg/m3)						
Maximum distance to flammable concentration (m)						
Maximum flammable mass (kg)	0					
Maximum area of flammable cloud (m2)	0					
at Time T (s)	0					
Flammable mass at time t (kg)	0					
Area flammable cloud at time t (m2)	0					
Volume of the flammable cloud at time t (m3)						
Height to LFL at time t (m)	0					
Length of flammable cloud at time t (m)	0					
Width of flammable cloud at time t (m)	0					
Offset flammable cloud at time t (m)	0					
Offset flammable cloud centre at time t (m)	0					
Contour Dimensions						
Concentration contours						
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]	
IDLH outer contour	5	0	0	8	6037,3	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	101 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - D5_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,37007				
Duration of the release (s)	609,94				
Pool surface area (m2)	50				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	5	0	0	8	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	102 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation -F2 30

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Use which representative rate First 20% average (flammable)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 250

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,23032

Purple book representative evaporation duration (s) 904,75

Representative temperature (°C) 28,626

Representative pool diameter (m) 7,9788

Density after mixing with air (kg/m3) 1,1885

Total evaporated mass (kg) 208,38

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 50

Schmidt number used 1,2736

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	103 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_0,5LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,23032
Duration of the release (s)	904,75
Pool surface area (m2)	50
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Reporting time flammable cloud	Time maximum area cloud
Concentration averaging time (s)	20
Use 50% LFL for cloud contour	Yes
Use mass between LFL and UFL	Yes
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	68,863
Concentration Results	
Flammability threshold concentration (mg/m3)	31394
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Maximum distance to flammable concentration (m)	1,4464
Maximum flammable mass (kg)	0
Maximum area of flammable cloud (m2)	0
at Time T (s)	0
Flammable mass at time t (kg)	0
Area flammable cloud at time t (m2)	0
Volume of the flammable cloud at time t (m3)	
Height to LFL at time t (m)	0,1
Length of flammable cloud at time t (m)	0
Width of flammable cloud at time t (m)	0
Offset flammable cloud at time t (m)	0
Offset flammable cloud centre at time t (m)	0

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	35	0	0	8	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	104 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Flammable Cloud - F2_LEL

Model: Neutral Gas - Flammable Cloud

version: v2021.02.f87b15d (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	ACETONE (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,23032				
Duration of the release (s)	904,75				
Pool surface area (m2)	50				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	NNE				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Reporting time flammable cloud	Time maximum area cloud				
Concentration averaging time (s)	20				
Use 50% LFL for cloud contour	No				
Use mass between LFL and UFL	Yes				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Concentration Results					
Flammability threshold concentration (mg/m3)	62788				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Maximum distance to flammable concentration (m)					
Maximum flammable mass (kg)	0				
Maximum area of flammable cloud (m2)	0				
at Time T (s)	0				
Flammable mass at time t (kg)	0				
Area flammable cloud at time t (m2)	0				
Volume of the flammable cloud at time t (m3)					
Height to LFL at time t (m)	0				
Length of flammable cloud at time t (m)	0				
Width of flammable cloud at time t (m)	0				
Offset flammable cloud at time t (m)	0				
Offset flammable cloud centre at time t (m)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH outer contour	35	0	0	8	6037,3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	105 di 169
Cod. HA	Descrizione	Rev.	Data	

D.2 STIMA DELL'IRRAGGIAMENTO TERMICO (ACETONE)

D.2.1 Pozza da 37 m²

Model: pool fire - Acetone (5 m/s) 20°C

Model: Pool Fire

version:

v2021.02.0caf297

(24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default
Source Definition	
Total mass released (kg)	4200
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	37
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003
Vulnerability	
Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ((sec*(W/m2)^n))	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333
Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	6,8637
Flame footprint dimensions D,-D,DMW,MW	9;-3;3;7
Calculated pool surface area (m2)	37
Combustion rate (kg/s)	1,406
Duration of fire (s)	2987,2
Surface emissive power flame (kW/m2)	31,245
Soot fraction used (-)	0,8
Flame tilt (deg)	56,016
Flame temperature (°C)	591,29
Length of the flame (m)	6,836
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	106 di 169
Cod. HA	Descrizione	Rev.	Data	

Weight ratio of SO ₂ /chemical (%)	0
Weight ratio of CO ₂ /chemical (%)	227,37
Weight ratio of H ₂ O/chemical (%)	93,091
Heat radiation at Xd (kW/m ²)	0,0036524
Atmospheric Transmissivity at Xd (%)	53,743
Viewfactor at Xd (%)	0,021751
Heat radiation dose at Xd (s*(kW/m ²) ^{4/3})	0,01125
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. [m]	DistMin. [m]	DistDist. [m]	WidthMax. [m]	WidthValue [%]
1 % lethality contour	10	-5	2	12	1

Heat Radiation Contours

Names	Max. [m]	DistMin. [m]	DistDist. [m]	WidthMax. [m]	WidthValue [kW/m ²]
37,5 kW/m ² heat radiation contour	0	0	0	0	37,5
12,5 kW/m ² heat radiation contour	10	-5	2	11	12,5
7 kW/m ² heat radiation contour	11	-6	2	14	7
5 kW/m ² heat radiation contour	12	-7	2	16	5
3 kW/m ² heat radiation contour	14	-8	2	19	3

Model: pool fire - Acetone (2 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B, ~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m²) 37

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO₂ in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ((sec*(W/m²)ⁿ)) -36,38

Heat radiation lethal damage Probit B 2,56

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	107 di 169
Cod. HA	Descrizione	Rev.	Data	

Heat radiation damage Probit N	1,3333
Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results

Fire Results

Equivalent diameter poolfire (m)	6,8637
Flame footprint dimensions D,-D,DMW,MW	9;-3;3;7
Calculated pool surface area (m2)	37
Combustion rate (kg/s)	1,406
Duration of fire (s)	2987,2
Surface emissive power flame (kW/m2)	29,035
Soot fraction used (-)	0,8
Flame tilt (deg)	43,304
Flame temperature (°C)	575,79
Length of the flame (m)	8,2865
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0053454
Atmospheric Transmissivity at Xd (%)	53,341
Viewfactor at Xd (%)	0,034514
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,018693
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	10	-5	2	13	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	9	-5	2	11	12,5
7 kW/m2 heat radiation contour	12	-6	2	15	7
5 kW/m2 heat radiation contour	13	-7	2	18	5
3 kW/m2 heat radiation contour	15	-9	2	22	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	108 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: pool fire - Acetone (5 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 37

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ((sec*(W/m2)^n)) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

Reporting

Reporting/receiver height (Zd) (m) 1,7

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m) 6,8637

Flame footprint dimensions D,-D,DMW,MW 9;-3;3;7

Calculated pool surface area (m2) 37

Combustion rate (kg/s) 1,406

Duration of fire (s) 2987,2

Surface emissive power flame (kW/m2) 30,945

Soot fraction used (-) 0,8

Flame tilt (deg) 55,907

Flame temperature (°C) 589,65

Length of the flame (m) 7,0078

Weight ratio of HCL/chemical (%) 0

Weight ratio of NO2/chemical (%) 0

Weight ratio of SO2/chemical (%) 0

Weight ratio of CO2/chemical (%) 227,37

Weight ratio of H2O/chemical (%) 93,091

Heat radiation at Xd (kW/m2) 0,0033887

Atmospheric Transmissivity at Xd (%) 48,904

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	109 di 169
Cod. HA	Descrizione	Rev.	Data	

Viewfactor at Xd (%)	0,022392
Heat radiation dose at Xd ($s \cdot (kW/m^2)^{4/3}$)	0,01018
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	10	-5	2	12	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	10	-4	2	10	12,5
7 kW/m2 heat radiation contour	11	-6	2	13	7
5 kW/m2 heat radiation contour	12	-7	2	15	5
3 kW/m2 heat radiation contour	14	-8	2	19	3

Model: pool fire - Acetone (2 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 4200

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 37

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ($(sec \cdot (W/m^2)^n)$) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

Reporting

Reporting/receiver height (Zd) (m) 1,7

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	110 di 169
Cod. HA	Descrizione	Rev.	Data	

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m)	6,8637
Flame footprint dimensions D,-D,DMW,MW	9;-3;3;7
Calculated pool surface area (m2)	37
Combustion rate (kg/s)	1,406
Duration of fire (s)	2987,2
Surface emissive power flame (kW/m2)	28,769
Soot fraction used (-)	0,8
Flame tilt (deg)	43,169
Flame temperature (°C)	574,31
Length of the flame (m)	8,4948
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0049398
Atmospheric Transmissivity at Xd (%)	48,422
Viewfactor at Xd (%)	0,03546
Heat radiation dose at Xd (s*(kW/m2)^4/3)	0,016826
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	10	-5	2	13	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	9	-5	1	11	12,5
7 kW/m2 heat radiation contour	11	-6	2	15	7
5 kW/m2 heat radiation contour	13	-7	2	17	5
3 kW/m2 heat radiation contour	15	-9	2	22	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	111 di 169
Cod. HA	Descrizione	Rev.	Data	

D.2.2 Pozza da 50 m²

Model: pool fire - Acetone (5 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters	
Inputs	
Process Conditions	
Chemical name	ACETONE (DIPPR)
Calculation Method	
Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default
Source Definition	
Total mass released (kg)	250
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	50
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Predefined wind direction	NNE
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003
Vulnerability	
Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ((sec*(W/m2)^n))	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333
Accuracy	
Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	7,9788
Flame footprint dimensions D,-D,DMW,MW	10;-4;3;8
Calculated pool surface area (m2)	50
Combustion rate (kg/s)	1,9
Duration of fire (s)	131,58
Surface emissive power flame (kW/m2)	31,737
Soot fraction used (-)	0,8
Flame tilt (deg)	55,501
Flame temperature (°C)	594,63
Length of the flame (m)	7,6359
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	112 di 169
Cod. HA	Descrizione	Rev.	Data	

Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0049324
Atmospheric Transmissivity at Xd (%)	53,887
Viewfactor at Xd (%)	0,028841
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,016792
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	12	-6	2	14	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	11	-5	2	12	12,5
7 kW/m2 heat radiation contour	13	-7	2	16	7
5 kW/m2 heat radiation contour	14	-8	2	18	5
3 kW/m2 heat radiation contour	16	-9	2	22	3

Model: pool fire - Acetone (2 m/s) 20°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 250

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 50

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 2

Predefined wind direction NNE

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ($(sec \cdot (W/m2)^n)$) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	113 di 169
Cod. HA	Descrizione	Rev.	Data	

Grid resolution	Medium
Reporting	
Reporting/receiver height (Zd) (m)	1,7
Reporting distance (Xd) (m)	200

Results	
Fire Results	
Equivalent diameter poolfire (m)	7,9788
Flame footprint dimensions D,-D,DMW,MW	10;-4;3;8
Calculated pool surface area (m2)	50
Combustion rate (kg/s)	1,9
Duration of fire (s)	131,58
Surface emissive power flame (kW/m2)	29,471
Soot fraction used (-)	0,8
Flame tilt (deg)	42,67
Flame temperature (°C)	578,92
Length of the flame (m)	9,2561
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0071817
Atmospheric Transmissivity at Xd (%)	53,479
Viewfactor at Xd (%)	0,045567
Heat radiation dose at Xd ($s \cdot (kW/m2)^{4/3}$)	0,027712
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions					
Lethality Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	12	-6	2	15	1
Heat Radiation Contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	10	-6	2	13	12,5
7 kW/m2 heat radiation contour	13	-7	2	17	7
5 kW/m2 heat radiation contour	15	-8	2	20	5
3 kW/m2 heat radiation contour	17	-10	2	25	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	114 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: pool fire - Acetone (5 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B,~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name ACETONE (DIPPR)

Calculation Method

Type of pool fire calculation Pool fire model Yellow Book

Type of pool fire source Instantaneous

Fraction combustion heat radiated (-) 0,35

Soot definition Calculate/Default

Source Definition

Total mass released (kg) 250

Temperature of the pool (°C) 20

Process Dimensions

Type of pool shape (pool fire) Circular

Max. pool surface poolfire (m2) 50

Height of the confined pool above ground level (m) 0

Include shielding at bottomside flame No

Meteo Definition

Wind speed at 10 m height (m/s) 5

Predefined wind direction NNE

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Amount of CO2 in atmosphere (-) 0,0003

Vulnerability

Maximum heat exposure duration (s) 20

Take protective effects of clothing into account No

Heat radiation lethal damage Probit A ((sec*(W/m2)^n)) -36,38

Heat radiation lethal damage Probit B 2,56

Heat radiation damage Probit N 1,3333

Accuracy

Grid resolution Medium

Reporting

Reporting/receiver height (Zd) (m) 1,7

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m) 7,9788

Flame footprint dimensions D,-D,DMW,MW 10;-4;3;8

Calculated pool surface area (m2) 50

Combustion rate (kg/s) 1,9

Duration of fire (s) 131,58

Surface emissive power flame (kW/m2) 31,43

Soot fraction used (-) 0,8

Flame tilt (deg) 55,391

Flame temperature (°C) 592,96

Length of the flame (m) 7,8278

Weight ratio of HCL/chemical (%) 0

Weight ratio of NO2/chemical (%) 0

Weight ratio of SO2/chemical (%) 0

Weight ratio of CO2/chemical (%) 227,37

Weight ratio of H2O/chemical (%) 93,091

Heat radiation at Xd (kW/m2) 0,0045784

Atmospheric Transmissivity at Xd (%) 49,067

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	115 di 169
Cod. HA	Descrizione	Rev.	Data	

Viewfactor at Xd (%)	0,029688
Heat radiation dose at Xd ($s \cdot (kW/m^2)^{4/3}$)	0,015205
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	12	-6	2	13	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	11	-5	2	12	12,5
7 kW/m2 heat radiation contour	13	-7	2	15	7
5 kW/m2 heat radiation contour	14	-7	2	18	5
3 kW/m2 heat radiation contour	16	-9	2	22	3

Model: pool fire - Acetone (2 m/s) 30°C

Model: Pool Fire

version: v2021.02.0caf297 (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Paragraph 6.5.4~Rew, P.J. & Hulbert, W.G. (1997) Modelling of Thermal radiation from external hydrocarbon poolfires, in Trans IChemE, Vol.75 part B, ~Rew, P.J. & Hulbert, W.G. (1996), Development of a pool fire thermal radiation model', HSE Contract research report no. 96, ~ Damage: Green Book 1st edition 1992, chapter 1 (Heat radiation); pages 11-36~

Parameters

Inputs

Process Conditions

Chemical name	ACETONE (DIPPR)
Calculation Method	

Type of pool fire calculation	Pool fire model Yellow Book
Type of pool fire source	Instantaneous
Fraction combustion heat radiated (-)	0,35
Soot definition	Calculate/Default

Source Definition

Total mass released (kg)	250
Temperature of the pool (°C)	20

Process Dimensions

Type of pool shape (pool fire)	Circular
Max. pool surface poolfire (m2)	50
Height of the confined pool above ground level (m)	0
Include shielding at bottomside flame	No

Meteo Definition

Wind speed at 10 m height (m/s)	2
Predefined wind direction	NNE

Environment

Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Amount of CO2 in atmosphere (-)	0,0003

Vulnerability

Maximum heat exposure duration (s)	20
Take protective effects of clothing into account	No
Heat radiation lethal damage Probit A ($(sec \cdot (W/m^2)^n)$)	-36,38
Heat radiation lethal damage Probit B	2,56
Heat radiation damage Probit N	1,3333

Accuracy

Grid resolution	Medium
-----------------	--------

Reporting

Reporting/receiver height (Zd) (m)	1,7
------------------------------------	-----

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	116 di 169
Cod. HA	Descrizione	Rev.	Data	

Reporting distance (Xd) (m) 200

Results

Fire Results

Equivalent diameter poolfire (m)	7,9788
Flame footprint dimensions D,-D,DMW,MW	10;-4;3;8
Calculated pool surface area (m2)	50
Combustion rate (kg/s)	1,9
Duration of fire (s)	131,58
Surface emissive power flame (kW/m2)	29,198
Soot fraction used (-)	0,8
Flame tilt (deg)	42,534
Flame temperature (°C)	577,4
Length of the flame (m)	9,4887
Weight ratio of HCL/chemical (%)	0
Weight ratio of NO2/chemical (%)	0
Weight ratio of SO2/chemical (%)	0
Weight ratio of CO2/chemical (%)	227,37
Weight ratio of H2O/chemical (%)	93,091
Heat radiation at Xd (kW/m2)	0,0066515
Atmospheric Transmissivity at Xd (%)	48,577
Viewfactor at Xd (%)	0,046896
Heat radiation dose at Xd (s*(kW/m2)^4/3)	0,025018
Percentage first degree burns at Xd (%)	0
Percentage second degree burns at Xd (%)	0
Percentage third degree burns at Xd (%)	0
Distance to clothing burning dose (m)	0

Contour Dimensions

Lethality Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [%]
1 % lethality contour	11	-6	2	14	1

Heat Radiation Contours

Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [kW/m2]
37,5 kW/m2 heat radiation contour	0	0	0	0	37,5
12,5 kW/m2 heat radiation contour	10	-5	2	13	12,5
7 kW/m2 heat radiation contour	13	-7	2	17	7
5 kW/m2 heat radiation contour	14	-8	2	20	5
3 kW/m2 heat radiation contour	17	-10	2	25	3

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	117 di 169
Cod. HA	Descrizione	Rev.	Data	

D.3 STIMA DEGLI EFFETTI DELLA DISPERSIONE DI VAPORI TOSSICI (METANOLO)

D.3.1 Pozza da 37 m³

Model: Pool evaporation - D5 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	First 20% average (flammable)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	2520
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	37
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	2
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,08526
Purple book representative evaporation duration (s)	1526,7
Representative temperature (°C)	19,987
Representative pool diameter (m)	6,6521
Density after mixing with air (kg/m3)	1,2015
Total evaporated mass (kg)	130,17
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	34,754
Schmidt number used	0,91478
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration - LC50

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	118 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,08526
Duration of the release (s)	1526,7
Pool surface area (m ²)	37
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m ³)	32375
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m ³)	32375
Concentration at (Xd, Yd, Zd, t) (mg/m ³)	69,445
Maximum concentration at Zd (mg/m ³)	707,21
...at distance (m)	8
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m ³)	
Contour Dimensions	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	119 di 169
Cod. HA	Descrizione	Rev.	Data	

Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,08526
Duration of the release (s)	1526,7
Pool surface area (m ²)	37
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	No
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m ³)	7993,8
Concentration at (Xd, Yd, Zd, t) (mg/m ³)	69,445
Maximum concentration at Zd (mg/m ³)	707,21
...at distance (m)	8
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,89223
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2984
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m ³)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	120 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,08526

Duration of the release (s) 1526,7

Pool surface area (m²) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 69,445

Maximum concentration at Zd (mg/m³) 707,21

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	121 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 2520

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 37

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 2

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,044859

Purple book representative evaporation duration (s) 1792,3

Representative temperature (°C) 20,282

Representative pool diameter (m) 6,8637

Density after mixing with air (kg/m3) 1,2018

Total evaporated mass (kg) 80,402

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 37

Schmidt number used 0,91478

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	122 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,044859

Duration of the release (s) 1792,3

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 385,68

Maximum concentration at Zd (mg/m3) 923,42

...at distance (m) 26,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	123 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,044859

Duration of the release (s) 1792,3

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 385,68

Maximum concentration at Zd (mg/m3) 923,42

...at distance (m) 26,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	124 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,044859
Duration of the release (s)	1792,3
Pool surface area (m ²)	37
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m ³)	799,38
Use dynamic concentration presentation	Yes

Results	
Meteo Definition	
Mixing height used (m)	68,863
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m ³)	799,38
Concentration at (Xd, Yd, Zd, t) (mg/m ³)	385,68
Maximum concentration at Zd (mg/m ³)	923,4
...at distance (m)	26,7
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m ³)	

Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m ³]
User defined concentration outer contour at 1.7m	45	15	18	4	799,38
User defined concentration at 1.7m at 600s	45	15	18	4	799,38

Model: Pool evaporation - D5 30 tossico

Model: Pool Evaporation

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	125 di 169
Cod. HA	Descrizione	Rev.	Data	

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	2520
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	37
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	40
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	2
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,092609
Purple book representative evaporation duration (s)	1696,8
Representative temperature (°C)	20,489
Representative pool diameter (m)	6,8637
Density after mixing with air (kg/m3)	1,1558
Total evaporated mass (kg)	157,14
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	37
Schmidt number used	0,91541
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4747
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	126 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,092609

Duration of the release (s) 1696,8

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 75,43

Maximum concentration at Zd (mg/m3) 768,17

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	127 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,092609

Duration of the release (s) 1696,8

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 75,43

Maximum concentration at Zd (mg/m3) 768,17

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	128 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,092609

Duration of the release (s) 1696,8

Pool surface area (m²) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 75,43

Maximum concentration at Zd (mg/m³) 768,17

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	129 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 2520

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 37

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 2

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,057175

Purple book representative evaporation duration (s) 1732,4

Representative temperature (°C) 25,146

Representative pool diameter (m) 6,8637

Density after mixing with air (kg/m3) 1,1564

Total evaporated mass (kg) 99,051

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 37

Schmidt number used 0,91541

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	130 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,057175

Duration of the release (s) 1732,4

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m3) 491,57

Maximum concentration at Zd (mg/m3) 1177

...at distance (m) 26,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	131 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,057175

Duration of the release (s) 1732,4

Pool surface area (m2) 37

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, $x/h < 15$.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 491,57

Maximum concentration at Zd (mg/m3) 1177

...at distance (m) 26,2

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	132 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	METHANOL (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,057175				
Duration of the release (s)	1732,4				
Pool surface area (m2)	37				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	N				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Time t after start release (s)	600				
Concentration averaging time (s)	600				
Reporting distance (Xd) (m)	100				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	799,38				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692				
Concentration Results					
Threshold concentration used (mg/m3)	799,38				
Concentration at (Xd, Yd, Zd, t) (mg/m3)	491,57				
Maximum concentration at Zd (mg/m3)	1176,9				
...at distance (m)	26,7				
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728				
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
User defined concentration outer contour at 1.7m	62	11	19	6	799,38
User defined concentration at 1.7m at 600s	62	11	15	6	799,38

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	133 di 169
Cod. HA	Descrizione	Rev.	Data	

D.3.2 Pozza da 50 m²

Model: Pool evaporation - D5 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Calculation Method	
Use which representative rate	Second 20% average (toxic)
Evaporation from land or water	Land
Type of release in pool	Instantaneous
Maximum evaluation time for evaporation (s)	1800
Source Definition	
Total mass released (kg)	150
Temperature of the pool (°C)	20
Process Dimensions	
Type of pool growth on Land	Spreading in bunds
Maximum pool surface area (m2)	50
Meteo Definition	
Wind speed at 10 m height (m/s)	5
Environment	
Temperature of the subsoil (°C)	20
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
Ambient relative humidity (%)	75
Solar radiation flux	Calculate value
Cloud cover (%)	0
Date: day number	20
Date: month number	6
North/South latitude of the location (deg)	44
Type of subsoil (evaporation)	Heavy concrete
Subsurface roughness description (pool)	flat sandy soil, concrete, tiles, plant-yard
Results	
Source Definition	
Time pool spreading ends (s)	4,5
Time until pool has totally evaporated (s)	
Purple book representative evaporation rate (kg/s)	0,052795
Purple book representative evaporation duration (s)	1474,9
Representative temperature (°C)	12,614
Representative pool diameter (m)	6,3449
Density after mixing with air (kg/m3)	1,2012
Total evaporated mass (kg)	77,865
... duration evaporation time (s)	1799,5
Corresponding representative pool surface area (m2)	31,619
Schmidt number used	0,91478
Dispersion model strategy	
Environment	
Heat flux from solar radiation (kW/m2)	1,4613
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	134 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,052795

Duration of the release (s) 1474,9

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 42,577

Maximum concentration at Zd (mg/m³) 376,76

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	135 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,052795

Duration of the release (s) 1474,9

Pool surface area (m2) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, $x/h < 15$.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m3) 42,577

Maximum concentration at Zd (mg/m3) 376,76

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	136 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,052795

Duration of the release (s) 1474,9

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 42,577

Maximum concentration at Zd (mg/m³) 376,76

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	137 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 20 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 150

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 20

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,040356

Purple book representative evaporation duration (s) 1587,4

Representative temperature (°C) 20,377

Representative pool diameter (m) 6,4734

Density after mixing with air (kg/m3) 1,2017

Total evaporated mass (kg) 64,061

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 32,912

Schmidt number used 0,91478

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4613

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	138 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,040356

Duration of the release (s) 1587,4

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 334,62

Maximum concentration at Zd (mg/m³) 718,25

...at distance (m) 27

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	139 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,040356
Duration of the release (s)	1587,4
Pool surface area (m2)	50
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	N
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	No
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	68,863
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	7993,8
Concentration at (Xd, Yd, Zd, t) (mg/m3)	334,62
Maximum concentration at Zd (mg/m3)	718,25
...at distance (m)	27
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	140 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,040356

Duration of the release (s) 1587,4

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 334,62

Maximum concentration at Zd (mg/m³) 718,33

...at distance (m) 27,4

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	141 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - D5 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 150

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 5

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,074528

Purple book representative evaporation duration (s) 1270,1

Representative temperature (°C) 19,737

Representative pool diameter (m) 6,2432

Density after mixing with air (kg/m3) 1,1557

Total evaporated mass (kg) 94,657

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 30,613

Schmidt number used 0,91541

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	142 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,074528

Duration of the release (s) 1270,1

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 60,104

Maximum concentration at Zd (mg/m³) 531,85

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	143 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,074528

Duration of the release (s) 1270,1

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration No

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 7993,8

Concentration at (Xd, Yd, Zd, t) (mg/m³) 60,104

Maximum concentration at Zd (mg/m³) 531,85

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	144 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,074528

Duration of the release (s) 1270,1

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 799,38

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m³) 799,38

Concentration at (Xd, Yd, Zd, t) (mg/m³) 60,104

Maximum concentration at Zd (mg/m³) 531,85

...at distance (m) 8

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,89223

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2984

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	145 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Pool evaporation - F2 30 tossico

Model: Pool Evaporation

version: v2021.02.8cf0fe9 (24/02/2021)

Reference: Yellow Book CPR14E 2nd Edition - Chapter 5: Evaporation. Trijssenaar-Buhre, I.J.M, Sterkenburg, R.P., Wijnant-Timmerman, S.I.: An advanced model for spreading and evaporation of accidentally released hazardous liquids on land. Diffusion coefficient in Schmidt number based on Fuller, Schetter and Gitting correlation, see <http://www.thermopedia.com/content/696>

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Calculation Method

Use which representative rate Second 20% average (toxic)

Evaporation from land or water Land

Type of release in pool Instantaneous

Maximum evaluation time for evaporation (s) 1800

Source Definition

Total mass released (kg) 150

Temperature of the pool (°C) 20

Process Dimensions

Type of pool growth on Land Spreading in bunds

Maximum pool surface area (m2) 50

Meteo Definition

Wind speed at 10 m height (m/s) 2

Environment

Temperature of the subsoil (°C) 40

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

Ambient relative humidity (%) 75

Solar radiation flux Calculate value

Cloud cover (%) 0

Date: day number 20

Date: month number 6

North/South latitude of the location (deg) 44

Type of subsoil (evaporation) Heavy concrete

Subsurface roughness description (pool) flat sandy soil, concrete, tiles, plant-yard

Results

Source Definition

Time pool spreading ends (s) 4,5

Time until pool has totally evaporated (s)

Purple book representative evaporation rate (kg/s) 0,058419

Purple book representative evaporation duration (s) 1398,4

Representative temperature (°C) 28,473

Representative pool diameter (m) 6,3754

Density after mixing with air (kg/m3) 1,1564

Total evaporated mass (kg) 81,69

... duration evaporation time (s) 1799,5

Corresponding representative pool surface area (m2) 31,923

Schmidt number used 0,91541

Dispersion model strategy

Environment

Heat flux from solar radiation (kW/m2) 1,4747

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	146 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LC50

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name METHANOL (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source Evaporating pool release

Mass flow rate of the source (kg/s) 0,058419

Duration of the release (s) 1398,4

Pool surface area (m²) 50

Process Dimensions

Height of release (Z-coordinate) (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction N

Environment

Ambient temperature (°C) 30

Ambient pressure (bar) 1,0133

North/South latitude of the location (deg) 44

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution Low

Reporting

Time t after start release (s) 600

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 100

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m³) 32375

Use dynamic concentration presentation Yes

Results

Meteo Definition

Mixing height used (m) 68,863

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m³) 32375

Concentration at (Xd, Yd, Zd, t) (mg/m³) 484,4

Maximum concentration at Zd (mg/m³) 1039,7

...at distance (m) 27

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,19728

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,28833

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m³)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	147 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - IDLH

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	METHANOL (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	Evaporating pool release
Mass flow rate of the source (kg/s)	0,058419
Duration of the release (s)	1398,4
Pool surface area (m2)	50
Process Dimensions	
Height of release (Z-coordinate) (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	N
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0133
North/South latitude of the location (deg)	44
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	Low
Reporting	
Time t after start release (s)	600
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	100
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	No
Use dynamic concentration presentation	Yes
Results	
Meteo Definition	
Mixing height used (m)	68,863
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	7993,8
Concentration at (Xd, Yd, Zd, t) (mg/m3)	484,4
Maximum concentration at Zd (mg/m3)	1039,7
...at distance (m)	27
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	148 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration - LOC

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters					
Inputs					
Process Conditions					
Chemical name	METHANOL (DIPPR)				
Source Definition					
Type of neutral gas release	Semi-continuous				
Type of continuos source	Evaporating pool release				
Mass flow rate of the source (kg/s)	0,058419				
Duration of the release (s)	1398,4				
Pool surface area (m2)	50				
Process Dimensions					
Height of release (Z-coordinate) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	N				
Environment					
Ambient temperature (°C)	30				
Ambient pressure (bar)	1,0133				
North/South latitude of the location (deg)	44				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Accuracy					
Grid resolution	Low				
Reporting					
Time t after start release (s)	600				
Concentration averaging time (s)	600				
Reporting distance (Xd) (m)	100				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	799,38				
Use dynamic concentration presentation	Yes				
Results					
Meteo Definition					
Mixing height used (m)	68,863				
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692				
Concentration Results					
Threshold concentration used (mg/m3)	799,38				
Concentration at (Xd, Yd, Zd, t) (mg/m3)	484,4				
Maximum concentration at Zd (mg/m3)	1039,9				
...at distance (m)	27,4				
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,19728				
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,28833				
Temperature after mixing and expansion (°C)					
Density after mixing and expansion (kg/m3)					
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
User defined concentration at 1.7m at 600s	59	13	17	6	799,38
User defined concentration outer contour at 1.7m	59	13	16	6	799,38

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	149 di 169
Cod. HA	Descrizione	Rev.	Data	

E TOP EVENT 8.B: ROTTURA/PERDITA DA TUBAZIONE DI TRASFERIMENTO

E.1 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)

E.1.1 Pozza da 37 m³

Model: Combustion and toxic combustion products 20°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (24/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters	
Inputs	
Process Conditions	
Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)
Calculation Method	
NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8
Source Definition	
Total mass released (kg)	2520
Surface of the fire (m ²)	37
Environment	
Ambient temperature (°C)	20
Results	
Process Conditions	
Averaged molecular formula used	C ₂ H ₄ Cl ₂
Source Definition	
Calculated molecular mass of the chemical (kg/kmol)	98,959
Fire Results	
Combustion rate of the chemical (kg/s)	1,4767
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	6,8637
(Convective) Heat production fire (MW)	6,5956
Duration of the fire (s)	1706,5
Total formation rate of combustion products (kg/s)	2,1821
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	1,0845
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,26522
H ₂ O formation rate (kg/s)	0,54294
Soot formation rate (kg/s)	0,2894
Height of the Flame (m)	9,7676
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	150 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Combustion and toxic combustion products 30°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (24/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters

Inputs

Process Conditions

Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)

Calculation Method

NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8

Source Definition

Total mass released (kg)	2520
Surface of the fire (m ²)	37

Environment

Ambient temperature (°C)	30
--------------------------	----

Results

Process Conditions

Averaged molecular formula used	C ₂ H ₄ Cl ₂
---------------------------------	---

Source Definition

Calculated molecular mass of the chemical (kg/kmol)	98,959
---	--------

Fire Results

Combustion rate of the chemical (kg/s)	1,5289
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	6,8637
(Convective) Heat production fire (MW)	6,8288
Duration of the fire (s)	1648,3
Total formation rate of combustion products (kg/s)	2,2593
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	1,1229
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,2746
H ₂ O formation rate (kg/s)	0,56214
Soot formation rate (kg/s)	0,29963
Height of the Flame (m)	9,9768

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	151 di 169
Cod. HA	Descrizione	Rev.	Data	

E.1.2 Pozza da 50 m³

Model: Combustion and toxic combustion products 20°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (24/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters	
Inputs	
Process Conditions	
Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)
Calculation Method	
NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8
Source Definition	
Total mass released (kg)	150
Surface of the fire (m ²)	50
Environment	
Ambient temperature (°C)	20
Results	
Process Conditions	
Averaged molecular formula used	C ₂ H ₄ Cl ₂
Source Definition	
Calculated molecular mass of the chemical (kg/kmol)	98,959
Fire Results	
Combustion rate of the chemical (kg/s)	1,9955
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	7,9788
(Convective) Heat production fire (MW)	8,9129
Duration of the fire (s)	75,169
Total formation rate of combustion products (kg/s)	2,9488
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	1,4656
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,35841
H ₂ O formation rate (kg/s)	0,73371
Soot formation rate (kg/s)	0,39108
Height of the Flame (m)	10,845
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	152 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Combustion and toxic combustion products 30°C

Model: Combustion and Toxic Combustion Products

version: v2021.02.9ce8d1b (24/02/2021)

Reference: Solids: Page 30 CPR 15/2 report TNO 94-316 proj. 24514 (including 35% conversion rate for NO₂). Liquids: Green Book 1992, chapter 4 page 9

Parameters	
Inputs	
Process Conditions	
Phase	Liquid
Chemical name	1,2-DICHLOROETHANE (DIPPR)
Calculation Method	
NO ₂ conversion fraction (-)	0,35
Fraction combustion heat radiated (-)	0,35
Fraction of soot (unburned carbon) (-)	0,8
Source Definition	
Total mass released (kg)	150
Surface of the fire (m ²)	50
Environment	
Ambient temperature (°C)	30
Results	
Process Conditions	
Averaged molecular formula used	C ₂ H ₄ Cl ₂
Source Definition	
Calculated molecular mass of the chemical (kg/kmol)	98,959
Fire Results	
Combustion rate of the chemical (kg/s)	2,0661
Heat of combustion material (kJ/kg)	11166
Equivalent diameter poolfire (m)	7,9788
(Convective) Heat production fire (MW)	9,228
Duration of the fire (s)	72,602
Total formation rate of combustion products (kg/s)	3,0531
NO ₂ formation rate (kg/s)	0
SO ₂ formation rate (kg/s)	0
HCl formation rate (kg/s)	1,5174
HBr formation rate (kg/s)	0
HF formation rate (kg/s)	0
CO ₂ formation rate (kg/s)	0,37108
H ₂ O formation rate (kg/s)	0,75965
Soot formation rate (kg/s)	0,40491
Height of the Flame (m)	11,077
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	153 di 169
Cod. HA	Descrizione	Rev.	Data	

E.2 INNALZAMENTO DEL PENNACCHIO

E.2.1 Pozza da 37 m³

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987). Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling. Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des. 67, 348-352.

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	1,0845				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	20				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	6,8637				
(Convective) Heat production fire (MW)	6,5956				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Max (center) height of plume (m)	83,043				
Distance to max plume height (m)	630,96				
Penetration fraction (-)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH at Zd	104	1	5	29	75,802
IDLH Max	207	1	91	32	75,802
User defined concentration Max	881	1	459	102	7,58
User defined concentration at Zd	263	1	116	49	7.58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	154 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires F2

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

0.01, 0.1, 0.5, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 5000, 10000, 20000, 50000, 100000, 200000, 500000, 1000000, 2000000, 5000000, 10000000, 20000000, 50000000, 100000000, 200000000, 500000000, 1000000000, 2000000000, 5000000000, 10000000000, 20000000000, 50000000000, 100000000000, 200000000000, 500000000000, 1000000000000, 2000000000000, 5000000000000, 10000000000000, 20000000000000, 50000000000000, 100000000000000, 200000000000000, 500000000000000, 1000000000000000, 2000000000000000, 5000000000000000, 10000000000000000, 20000000000000000, 50000000000000000, 100000000000000000, 200000000000000000, 500000000000000000, 1000000000000000000, 2000000000000000000, 5000000000000000000, 10000000000000000000, 20000000000000000000, 50000000000000000000, 100000000000000000000, 200000000000000000000, 500000000000000000000, 1000000000000000000000, 2000000000000000000000, 5000000000000000000000, 10000000000000000000000, 20000000000000000000000, 50000000000000000000000, 100000000000000000000000, 200000000000000000000000, 500000000000000000000000, 1000000000000000000000000, 2000000000000000000000000, 5000000000000000000000000, 10000000000000000000000000, 20000000000000000000000000, 50000000000000000000000000, 100000000000000000000000000, 200000000000000000000000000, 500000000000000000000000000, 1000000000000000000000000000, 2000000000000000000000000000, 5000000000000000000000000000, 10000000000000000000000000000, 20000000000000000000000000000, 50000000000000000000000000000, 100000000000000000000000000000, 200000000000000000000000000000, 500000000000000000000000000000, 1000000000000000000000000000000, 2000000000000000000000000000000, 5000000000000000000000000000000, 10000000000000000000000000000000, 20000000000000000000000000000000, 50000000000000000000000000000000, 100000000000000000000000000000000, 200000000000000000000000000000000, 500000000000000000000000000000000, 1000000000000000000000000000000000, 2000000000000000000000000000000000, 5000000000000000000000000000000000, 10000000000000000000000000000000000, 20000000000000000000000000000000000, 50000000000000000000000000000000000, 100000000000000000000000000000000000, 200000000000000000000000000000000000, 500000000000000000000000000000000000, 1000000000000000000000000000000000000, 2000000000000000000000000000000000000, 5000000000000000000000000000000000000, 10000000000000000000000000000000000000, 20000000000000000000000000000000000000, 50000000000000000000000000000000000000, 100000000000000000000000000000000000000, 200000000000000000000000000000000000000, 500000000000000000000000000000000000000, 1000000000000000000000000000000000000000, 2000000000000000000000000000000000000000, 5000000000000000000000000000000000000000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100,

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	155 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987). Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling. Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

PCS: 07, 040-032.

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	1,1229				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	30				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	6,8637				
(Convective) Heat production fire (MW)	6,8288				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Max (center) height of plume (m)	84,912				
Distance to max plume height (m)	630,96				
Penetration fraction (-)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH Max	211	1	95	33	75,802
IDLH at Zd	103	1	5	29	75,802
User defined concentration at Zd	259	1	117	49	7,58
User defined concentration Max	902	1	433	103	7,58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	156 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires F2

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

0.01, 0.1, 0.5, 1, 2, 5, 10, 20, 50, 100, 200, 500, 1000, 2000, 5000, 10000, 20000, 50000, 100000, 200000, 500000, 1000000, 2000000, 5000000, 10000000, 20000000, 50000000, 100000000, 200000000, 500000000, 1000000000, 2000000000, 5000000000, 10000000000, 20000000000, 50000000000, 100000000000, 200000000000, 500000000000, 1000000000000, 2000000000000, 5000000000000, 10000000000000, 20000000000000, 50000000000000, 100000000000000, 200000000000000, 500000000000000, 1000000000000000, 2000000000000000, 5000000000000000, 10000000000000000, 20000000000000000, 50000000000000000, 100000000000000000, 200000000000000000, 500000000000000000, 1000000000000000000, 2000000000000000000, 5000000000000000000, 10000000000000000000, 20000000000000000000, 50000000000000000000, 100000000000000000000, 200000000000000000000, 500000000000000000000, 1000000000000000000000, 2000000000000000000000, 5000000000000000000000, 10000000000000000000000, 20000000000000000000000, 50000000000000000000000, 100000000000000000000000, 200000000000000000000000, 500000000000000000000000, 1000000000000000000000000, 2000000000000000000000000, 5000000000000000000000000, 10000000000000000000000000, 20000000000000000000000000, 50000000000000000000000000, 100000000000000000000000000, 200000000000000000000000000, 500000000000000000000000000, 1000000000000000000000000000, 2000000000000000000000000000, 5000000000000000000000000000, 10000000000000000000000000000, 20000000000000000000000000000, 50000000000000000000000000000, 100000000000000000000000000000, 200000000000000000000000000000, 500000000000000000000000000000, 1000000000000000000000000000000, 2000000000000000000000000000000, 5000000000000000000000000000000, 10000000000000000000000000000000, 20000000000000000000000000000000, 50000000000000000000000000000000, 100000000000000000000000000000000, 200000000000000000000000000000000, 500000000000000000000000000000000, 1000000000000000000000000000000000, 2000000000000000000000000000000000, 5000000000000000000000000000000000, 10000000000000000000000000000000000, 20000000000000000000000000000000000, 50000000000000000000000000000000000, 100000000000000000000000000000000000, 200000000000000000000000000000000000, 500000000000000000000000000000000000, 1000000000000000000000000000000000000, 2000000000000000000000000000000000000, 5000000000000000000000000000000000000, 10000000000000000000000000000000000000, 20000000000000000000000000000000000000, 50000000000000000000000000000000000000, 100000000000000000000000000000000000000, 200000000000000000000000000000000000000, 500000000000000000000000000000000000000, 1000000000000000000000000000000000000000, 2000000000000000000000000000000000000000, 5000000000000000000000000000000000000000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100, 200, 500, 1000, 2000, 5000, 100,

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	157 di 169
Cod. HA	Descrizione	Rev.	Data	

E.2.2 Pozza da 50 m³

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987). Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling. Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	1,4656				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	20				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	7,9788				
(Convective) Heat production fire (MW)	8,9129				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Max (center) height of plume (m)	99,689				
Distance to max plume height (m)	691,83				
Penetration fraction (-)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH at Zd	105	1	5	33	75,802
IDLH Max	240	1	103	37	75,802
User defined concentration at Zd	246	1	101	51	7,58
User defined concentration Max	1035	1	497	117	7,58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	158 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires F2

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des. 67, 348-352.

002, 01, 010 002:

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	1,4656				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	F (Very Stable)				
Wind speed at 10 m height (m/s)	2				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	20				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	7,9788				
(Convective) Heat production fire (MW)	8,9129				
Results					
Meteo Definition					
Mixing height used (m)	69,499				
Concentration Results					
Max (center) height of plume (m)	72,508				
Distance to max plume height (m)	2290,9				
Penetration fraction (-)	0,54559				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH Max	881	1	414	50	75,802
IDLH at Zd	18	1	1	31	75,802
User defined concentration at Zd	23	1	1	35	7,58
User defined concentration Max	4365	1	2272	202	7.58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	159 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Plume Rise from Fires D5

Model: Plume Rise from Fires

version: v2021.02.1efd91c (24/02/2021)

Reference: Yellow Book. (2nd Edition, 1992). Methods for the calculation of Physical Effects. The Hague: CPR14E. Mills, M. (November 1987).

Modelling the release and dispersion of toxic combustion products from chemical fires. International Conference on Vapour Cloud Modeling.

Boston, MA. Carter, D. (1989). Methods for estimating the dispersion of toxic combustion products from large fires. Chemical Engineering Res. Des, 67, 348-352.

001, 01, 010 002:

Parameters					
Inputs					
Process Conditions					
Chemical name	HYDROGEN CHLORIDE (DIPPR)				
Source Definition					
Mass flow rate of the source (kg/s)	1,5174				
Process Dimensions					
Release height (Stack height) (m)	0				
Meteo Definition					
Meteorological data	Pasquill				
Pasquill stability class	D (Neutral)				
Wind speed at 10 m height (m/s)	5				
Predefined wind direction	User defined				
Wind comes from (North = 0 degrees) (deg)	270				
Environment					
Ambient temperature (°C)	30				
North/South latitude of the location (deg)	43				
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.				
Reporting					
Concentration averaging time (s)	600				
Reporting/receiver height (Zd) (m)	1,7				
Predefined concentration	User defined				
User defined threshold concentration (mg/m3)	7,58				
End point for graphs (m)	10000				
Fire Results					
(Representative) Diameter of fire (m)	7,9788				
(Convective) Heat production fire (MW)	9,228				
Results					
Meteo Definition					
Mixing height used (m)	500				
Concentration Results					
Max (center) height of plume (m)	101,93				
Distance to max plume height (m)	724,44				
Penetration fraction (-)	0				
Contour Dimensions					
Concentration contours					
Names	Max. Dist [m]	Min. Dist [m]	Dist. Width [m]	Max. Width [m]	Value [mg/m3]
IDLH Max	246	1	111	37	75,802
IDLH at Zd	104	1	5	33	75,802
User defined concentration at Zd	241	1	94	51	7,58
User defined concentration Max	1059	1	519	119	7,58

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	160 di 169
Cod. HA	Descrizione	Rev.	Data	

E.3 VALUTAZIONE DELLA DISPERSIONE DEI PRODOTTI DI COMBUSTIONE (ACIDO CLORIDRICO)

E.3.1 Pozza da 37 m³

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill D5 20°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,0845
Duration of the release (s)	1706,5
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	83,043
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,29071
Maximum concentration at Zd (mg/m3)	2,4745
...at distance (m)	945,3
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,84752
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2681
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	162 di 169
Cod. HA	Descrizione	Rev.	Data	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 20°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name HYDROGEN CHLORIDE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source User defined window

Mass flow rate of the source (kg/s) 1,0845

Duration of the release (s) 1706,5

Length source in wind (x) direction (m) 0

Width source in crosswind (y) direction (m) 0

Height source in vertical (z) direction (m) 0

Process Dimensions

Height of release (Z-coordinate) (m) 65,876

Offset X direction (distance) start dispersion (m) 0

Offset Z direction (height) start dispersion (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class F (Very Stable)

Wind speed at 10 m height (m/s) 2

Predefined wind direction User defined

Wind comes from (North = 0 degrees) (deg) 270

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0151

North/South latitude of the location (deg) 43

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution High

Reporting

Time t after start release (s) 1800

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 10000

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 7,58

Use dynamic concentration presentation No

Results

Meteo Definition

Mixing height used (m) 69,499

Inverse Monin-Obukhov length (1/L) used (1/m) 0,050692

Concentration Results

Threshold concentration used (mg/m3) 7,58

Concentration at (Xd, Yd, Zd, t) (mg/m3) 2,8475

Maximum concentration at Zd (mg/m3) 3,5787

...at distance (m) 4778

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,045041

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 0,065828

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	163 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill D5 30°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,1229
Duration of the release (s)	1648,3
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	84,912
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,29897
Maximum concentration at Zd (mg/m3)	2,3535
...at distance (m)	945,3
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,84649
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2674
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 30°C

Model: Neutral Gas - Concentration

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	164 di 169
Cod. HA	Descrizione	Rev.	Data	

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters**Inputs****Process Conditions**

Chemical name	HYDROGEN CHLORIDE (DIPPR)
---------------	---------------------------

Source Definition

Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,1229
Duration of the release (s)	1648,3
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0

Process Dimensions

Height of release (Z-coordinate) (m)	67,524
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0

Meteo Definition

Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270

Environment

Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution	High
-----------------	------

Reporting

Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No

Results**Meteo Definition**

Mixing height used (m)	69,499
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692

Concentration Results

Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	2,8946
Maximum concentration at Zd (mg/m3)	3,6099
...at distance (m)	4778
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,033258
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,048607
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	165 di 169
Cod. HA	Descrizione	Rev.	Data	

E.3.2 Pozza da 50 m³

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill D5 20°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters

Inputs

Process Conditions

Chemical name HYDROGEN CHLORIDE (DIPPR)

Source Definition

Type of neutral gas release Semi-continuous

Type of continuous source User defined window

Mass flow rate of the source (kg/s) 1,4656

Duration of the release (s) 75,169

Length source in wind (x) direction (m) 0

Width source in crosswind (y) direction (m) 0

Height source in vertical (z) direction (m) 0

Process Dimensions

Height of release (Z-coordinate) (m) 99,689

Offset X direction (distance) start dispersion (m) 0

Offset Z direction (height) start dispersion (m) 0

Meteo Definition

Meteorological data Pasquill

Pasquill stability class D (Neutral)

Wind speed at 10 m height (m/s) 5

Predefined wind direction User defined

Wind comes from (North = 0 degrees) (deg) 270

Environment

Ambient temperature (°C) 20

Ambient pressure (bar) 1,0151

North/South latitude of the location (deg) 43

Roughness length description Parkland, bushes; numerous obstacles, x/h < 15.

Accuracy

Grid resolution High

Reporting

Time t after start release (s) 1800

Concentration averaging time (s) 600

Reporting distance (Xd) (m) 10000

Reporting/receiver height (Zd) (m) 1,7

Predefined concentration User defined

User defined threshold concentration (mg/m3) 7,58

Use dynamic concentration presentation No

Results

Meteo Definition

Mixing height used (m) 500

Inverse Monin-Obukhov length (1/L) used (1/m) 0

Concentration Results

Threshold concentration used (mg/m3) 7,58

Concentration at (Xd, Yd, Zd, t) (mg/m3) 0,0010862

Maximum concentration at Zd (mg/m3) 3,2888

...at distance (m) 1384

Stand. dev. of turbulent velocity in vert. direction used (m/s) 0,83828

Stand. dev. of turbulent velocity in horiz. direction used (m/s) 1,2619

Temperature after mixing and expansion (°C)

Density after mixing and expansion (kg/m3)

Contour Dimensions

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	166 di 169
Cod. HA	Descrizione	Rev.	Data	

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 20°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)

Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,4656
Duration of the release (s)	75,169
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	69
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	20
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	69,499
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,028974
Maximum concentration at Zd (mg/m3)	2,8785
...at distance (m)	4009,2
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,01672
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,024437
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill D5 30°C

Model: Neutral Gas - Concentration

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	167 di 169
Cod. HA	Descrizione	Rev.	Data	

version: v2021.02.022757e (24/02/2021)
Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	
Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,5174
Duration of the release (s)	72,602
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	101,93
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	D (Neutral)
Wind speed at 10 m height (m/s)	5
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No

Results	
Meteo Definition	
Mixing height used (m)	500
Inverse Monin-Obukhov length (1/L) used (1/m)	0
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,001008
Maximum concentration at Zd (mg/m3)	3,1658
...at distance (m)	1384
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,83702
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	1,2611
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	

Contour Dimensions

Model: Neutral Gas Dispersion: Concentration HCl - Classe di Pasquill F2 30°C

Model: Neutral Gas - Concentration

version: v2021.02.022757e (24/02/2021)
Reference: Yellow Book (CPR-14E), 3rd edition 1997, Chapter 4

Parameters	
Inputs	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	168 di 169
Cod. HA	Descrizione	Rev.	Data	

Process Conditions	
Chemical name	HYDROGEN CHLORIDE (DIPPR)
Source Definition	
Type of neutral gas release	Semi-continuous
Type of continuous source	User defined window
Mass flow rate of the source (kg/s)	1,5174
Duration of the release (s)	72,602
Length source in wind (x) direction (m)	0
Width source in crosswind (y) direction (m)	0
Height source in vertical (z) direction (m)	0
Process Dimensions	
Height of release (Z-coordinate) (m)	69
Offset X direction (distance) start dispersion (m)	0
Offset Z direction (height) start dispersion (m)	0
Meteo Definition	
Meteorological data	Pasquill
Pasquill stability class	F (Very Stable)
Wind speed at 10 m height (m/s)	2
Predefined wind direction	User defined
Wind comes from (North = 0 degrees) (deg)	270
Environment	
Ambient temperature (°C)	30
Ambient pressure (bar)	1,0151
North/South latitude of the location (deg)	43
Roughness length description	Parkland, bushes; numerous obstacles, x/h < 15.
Accuracy	
Grid resolution	High
Reporting	
Time t after start release (s)	1800
Concentration averaging time (s)	600
Reporting distance (Xd) (m)	10000
Reporting/receiver height (Zd) (m)	1,7
Predefined concentration	User defined
User defined threshold concentration (mg/m3)	7,58
Use dynamic concentration presentation	No
Results	
Meteo Definition	
Mixing height used (m)	69,499
Inverse Monin-Obukhov length (1/L) used (1/m)	0,050692
Concentration Results	
Threshold concentration used (mg/m3)	7,58
Concentration at (Xd, Yd, Zd, t) (mg/m3)	0,028834
Maximum concentration at Zd (mg/m3)	2,9111
...at distance (m)	3981,6
Stand. dev. of turbulent velocity in vert. direction used (m/s)	0,01672
Stand. dev. of turbulent velocity in horiz. direction used (m/s)	0,024437
Temperature after mixing and expansion (°C)	
Density after mixing and expansion (kg/m3)	
Contour Dimensions	

CO 05 RA VA 00 RP DT 10.00	Appendice E.1	00	26/03/2021	169 di 169
Cod. HA	Descrizione	Rev.	Data	